

NETWORK CAMERAS					
Fixed Cameras					
AXIS M1011		0302-002	384708	Small-sized indoor network camera. Fixed lens. 1/4" progressive scan CMOS sensor. Multiple, individually configurable H.264, Motion JPEG and MPEG-4 Part 2 streams; max VGA 640 x 480 resolution at 30 fps. Video motion detection. Includes stand and clamp for easy mounting, and power supply.	149
AXIS M1011 10-pack/bulk		0302-022	384708-10PK	AXIS M1011 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included. No clamps.	1 469
AXIS M1011 Surveillance Kit		0302-042	390052	Bundle with 4 units of AXIS M1011 and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	699
AXIS M1011-W		0301-002	384709	Small-sized indoor network camera. Fixed lens. 1/4" progressive scan CMOS sensor. Connects over wireless LAN (IEEE 802.11g) or wired Ethernet. Multiple, individually configurable H.264, Motion JPEG and MPEG-4 Part 2 streams; max VGA 640 x 480 resolution at 30 fps. Video motion detection. Includes stand and clamp for easy mounting, and power supply.	169
AXIS M1011-W 10-pack/bulk		0301-022	384709-10PK	AXIS M1011-W in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included. No clamps.	1 669
AXIS M1031-W		0300-002	384710	Small-sized indoor network camera. Fixed lens. 1/4" progressive scan CMOS sensor. Connects over wireless LAN (IEEE 802.11g) or wired Ethernet. Multiple, individually configurable H.264, Motion JPEG and MPEG-4 Part 2 streams; max VGA 640 x 480 resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Passive infrared (PIR) sensor and white LED illuminator integrated. Includes stand and clamp for easy mounting, and power supply.	229
AXIS M1031-W 10-pack/bulk		0300-022	384710-10PK	AXIS M1031-W in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies included. No clamps.	2 259
AXIS M1031-W Surveillance Kit		0300-042	390054	Bundle with 4 units of AXIS M1031-W and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	999
AXIS M1043-W		0446-002	454468	Small-sized indoor network camera. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA 800 x 600 resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Integrated passive infrared (PIR) sensor, white LED illuminator and I/O ports. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup. MicroSD/SDHC memory card slot for edge storage. Includes stand and clamp for easy mounting, optional extension for stand and power supply.	239
AXIS M1044-W		0447-002	454469	Small-sized indoor network camera. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Integrated passive infrared (PIR) sensor, white LED illuminator and I/O ports. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup. MicroSD/SDHC memory card slot for edge storage. Includes stand and clamp for easy mounting, optional extension for stand and power supply.	299
AXIS M1103 2.8MM		0329-001	418107	SVGA camera with fixed, 2.8 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	269
AXIS M1103 2.8MM BULK 10PCS		0329-021	418107-10PK	AXIS M1103 2.8MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	2 659
AXIS M1103 2.8MM SURVEILLANCE KIT		0329-041	421812	Bundle with 4 units of AXIS M1103 2.8mm and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 099

AXIS M1103 6.0MM		0366-001	418108	SVGA camera with fixed, 6.0 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	269
AXIS M1103 6.0MM BULK 10PCS		0366-021	418108-10PK	AXIS M1103 6.0MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	2 659
AXIS M1103 BAREB BULK 10PCS		0329-031	422071	AXIS M1103 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	2 529
AXIS M1104 2.8MM		0339-001	418110	HDTV camera with fixed, 2.8 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	349
AXIS M1104 2.8MM BULK 10PCS		0339-021	418110-10PK	AXIS M1104 2.8MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	3 459
AXIS M1104 2.8MM SURVEILLANCE KIT		0339-041	421814	Bundle with 4 units of AXIS M1104 2.8mm and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 399
AXIS M1104 6.0MM		0367-001	418111	HDTV camera with fixed, 6.0 mm, CS-mount lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	349
AXIS M1104 6.0MM BULK 10PCS		0367-021	418111-10PK	AXIS M1104 6.0MM in 10-pack. Cannot be sold separately as single packs. Midspans not included.	3 459
AXIS M1104 BAREB BULK 10PCS		0339-031	422074	AXIS M1104 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	3 329
AXIS M1113		0340-001	418113	SVGA camera with varifocal 2.9-8.2 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	349
AXIS M1113 BULK 10PCS		0340-021	418113-10PK	AXIS M1113 in 10-pack. Cannot be sold separately as single packs. Midspans not included.	3 459
AXIS M1113 BAREB BULK 10PCS		0340-031	422076	AXIS M1113 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	3 259
AXIS M1113-E		0431-001	441850	Outdoor, IP66-rated SVGA camera with varifocal 2.9-8.2 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Operation in -20°C to +50°C (-4 °F to 122 °F). Power over Ethernet. Includes a removable sunshield and wall bracket. Midspan not included.	429
AXIS M1114		0341-001	418117	HDTV camera with varifocal 2.8-8 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	429
AXIS M1114 BULK 10PCS		0341-021	418117-10PK	AXIS M1114 in 10-pack. Cannot be sold separately as single packs. Midspans not included.	4 259
AXIS M1114 BAREB BULK 10PCS		0341-031	422075	AXIS M1114 Barebone in 10-pack. Cannot be sold separately as single packs. No midspans. No lens.	4 019
AXIS M1114-E		0432-001	441851	Outdoor, IP66-rated HDTV camera with varifocal 2.8-8 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection and active tampering alarm. Operation in -20°C to +50°C (-4 °F to 122 °F). Power over Ethernet. Includes a removable sunshield and wall bracket. Midspan not included.	509
AXIS M1054		0338-002	416400	Small-sized indoor network camera. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Two-way audio with built-in microphone and speaker. Video motion and audio detection. Integrated passive infrared (PIR) sensor, white LED illuminator and I/O ports. Powered over Ethernet or by power supply. Includes stand and clamp for easy mounting, optional extension for stand and power supply.	309
AXIS M1054 BULK 10PCS		0338-021	430058	AXIS M1054 in 10-pack/bulk. Cannot be sold separately as single packs. Power supplies, clamps and stand extensions not included.	3 059
AXIS M1054 SURVEILLANCE KIT		0338-042	421817	Bundle with 4 units of AXIS M1054 and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 299
AXIS 210A	EOL	0233-002	319390	Indoor camera, fixed lens. 1/4" progressive scan CCD. Up to VGA 640x480 resolution at 30 fps frame rate. Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Audio full duplex G.711 with built-in microphone. Includes adjustable stand and power supply.	419
AXIS 210A 10-pack/bulk	EOL	0233-022	324008	AXIS 210A in 10-pack. Cannot be sold separately. Power supplies included	4 149
AXIS 210A Surveillance Kit	EOL	0233-062	332759	Bundle with 4 units of AXIS 210A and a 4-license AXIS Camera Station surveillance software for video monitoring, recording and event management. Note: Multiple orders of this SKU will not result in 8-, 12-, 16-license, etc of ACS. Additional cameras and ACS 1 or 5 upgrade licenses must be ordered separately.	1 849
AXIS 210A Barebone 10-pack	EOL	0233-052	324504	AXIS 210A Barebone in 10-pack. Cannot be sold separately. Power supplies included.	4 039

AXIS P1311	EOL	0293-002	382751	Fixed, CS-mount lens , 1/4" progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max VGA 640 x 480 resolution at 30 fps. MPEG-4 Part 2 also supported. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet . Includes power supply.	419
AXIS P1311 10-pack/bulk	EOL	0293-021	382751-10PK	AXIS P1311 in 10-pack. Cannot be sold separately as single packs . No power supplies.	4 119
AXIS P1311 Barebone 10-pack/bulk	EOL	0293-051	390830	AXIS P1311 Barebone in 10-pack. Cannot be sold separately as single packs . No power supplies. No lens.	4 009
AXIS P1343		0320-001	402498	SVGA, day/night, fixed camera with varifocal 3-8 mm DC-iris lens and remote back focus . Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR . Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet . Power supply not included .	569
AXIS P1343 10-pack/bulk		0320-021	402498-10PK	AXIS P1343 in 10-pack. Cannot be sold separately as single packs . No power supplies.	5 589
AXIS P1343 Barebone 10-pack/bulk		0320-051	413508	AXIS P1343 Barebone in 10-pack. Cannot be sold separately as single packs . No power supplies.	5 299
AXIS P1343-E		0349-001	418120	Outdoor, IP66-rated, SVGA, day/night, network camera with varifocal 3-8 mm DC-iris lens and remote back focus . Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR . Video motion detection and active tampering alarm. Two-way audio . SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af compliant midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan . Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included .	769
AXIS P1344		0324-001	402499	HDTV, day/night, fixed camera with varifocal 3-8 mm DC-iris lens and remote back focus . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR . Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet . Power supply not included .	649
AXIS P1344 10-pack/bulk		0324-021	413509	AXIS P1344 in 10-pack. Cannot be sold separately as single packs . No power supplies.	6 389
AXIS P1344 Barebone 10-pack/bulk		0324-051	413510	AXIS P1344 Barebone in 10-pack. Cannot be sold separately as single packs . No power supplies.	5 969
AXIS P1344-E		0350-001	418121	Outdoor, IP66-rated, HDTV, day/night, fixed network camera with varifocal 3-8 mm DC-iris lens and remote back focus . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR . Video motion detection and active tampering alarm. Two-way audio . SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan . Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included .	849
AXIS P1346		0328-001	402500	HDTV, day/night, fixed camera with varifocal 4-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps, or HDTV 1080p at 30 fps . Digital PTZ support includes multi-view streaming of different view areas. WDR . Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet . Power supply not included .	849
AXIS P1346 10-pack/bulk		0328-021	402500-10PK	AXIS P1346 in 10-pack. Cannot be sold separately as single packs . No power supplies.	8 389
AXIS P1346 Barebone 10-pack/bulk		0328-051	416479	AXIS P1346 Barebone in 10-pack. Cannot be sold separately as single packs . No power supplies.	7 969
AXIS P1346-E		0351-001	418122	Outdoor, IP66-rated, HDTV, day/night, fixed camera with varifocal 4-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps, or HDTV 1080p at 30 fps . Digital PTZ support includes multi-view streaming of different view areas. WDR . Video motion detection and active tampering alarm. Two-way audio . SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan . Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included .	1 099
AXIS P1347		0343-001	424651	5MP, day/night, fixed camera with varifocal 3.5-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps . Digital PTZ support includes multi-view streaming of different view areas. WDR . Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet . Power supply not included .	1 099

AXIS P1347-E		0368-001	422145	Outdoor, IP66-rated, 5MP, day/night, fixed camera with varifocal 3.5-10 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps, 3MP resolution at 20 fps, or HDTV 1080p at 30 fps. Digital PTZ support includes multi-view streaming of different view areas. WDR. Video motion detection and active tampering alarm. Two-way audio. SD/SDHC memory card slot for optional local video storage. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included.	1 349
AXIS P1347 BAREBONE BULK 10PCS		0343-051	443945	AXIS P1347 Barebone in 10-pack. Cannot be sold separately as single packs. No power supplies.	10 249
AXIS P1347 BULK 10PCS		0343-021	443946	AXIS P1347 in 10-pack. Cannot be sold separately as single packs. No power supplies.	10 889
AXIS Q1602		0437-001	448506	Extended D1 (768x576) resolution, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Lightfinder technology. Support for P-Iris, multiple, individually configurable H.264 and Motion JPEG streams; Extended D1 resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Power supply not included.	849
AXIS Q1602-E		0438-001	448507	Outdoor, IP66-rated, Extended D1 (768x576) resolution, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Lightfinder technology. Support for P-Iris, multiple, individually configurable H.264 and Motion JPEG streams; Extended D1 resolution at 30 fps. WDR – dynamic contrast. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Arctic Temperature Control, Operation in -30°C to +50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40°C to +50°C (-40 °F to 122 °F) with High PoE Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1 099
AXIS Q1604-E		0463-001	452414	Outdoor, IP66-rated HDTV, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Support for P-Iris, Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at full frame rate. WDR-dynamic contrast and WDR-dynamic capture. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Arctic Temperature Control, Operation in -30°C to +50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40°C to +50°C (-40 °F to 122 °F) with High PoE Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1 099
AXIS Q1604		0439-001	452415	HDTV, day/night, fixed camera with varifocal 2.8-8 mm DC-iris lens and remote back focus. Support for P-Iris, Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at full frame rate. WDR-dynamic contrast and WDR-dynamic capture. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Power supply not included.	849
AXIS 211A	EOL	0223-002	307060	Varifocal DC-iris lens. 1/4" progressive scan CCD. Down to 0.75 lux. Up to VGA 640x480 resolution at full 30 fps frame rate. Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Audio full duplex G.711 with built-in microphone. Power over Ethernet. Includes adjustable stand and power supply.	499
AXIS 211A 10-pack	EOL	0223-022	324007	AXIS 211A in 10-pack. Cannot be sold separately. Power supplies included.	4 919
AXIS 211A Barebone 10-pack	EOL	0223-052	360694	AXIS 211A Barebone in 10-pack.	4 669
AXIS 211M	EOL	0269-002	349088	1.3 Megapixel 1/3" progressive scan CMOS sensor. Varifocal DC-iris F1.0 lens. Simultaneous Motion JPEG and MPEG-4 in full megapixel 1280x1024 resolution. 12 frames per second in full resolution, 30 frames per second in partial scan 800x600. Video Motion Detection and I/O for alarm/event handling. Two-way, full duplex audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes adjustable stand and power supply.	579
AXIS 211M 10-pack	EOL	0269-021	360977	AXIS 211M in 10-pack. Cannot be sold separately. No power supplies.	5 689
AXIS 211M Barebone 10-pack/bulk	EOL	0269-051	400948	AXIS 211M Barebone in 10-pack. Cannot be sold separately as single packs. No power supplies.	5 389
AXIS 211M Outdoor Verso Bundle	EOL	0269-031	358675	Bundle with 1 unit of AXIS 211M and Verso outdoor housing (0217-001). Including wall mount (0217-031) and power supply (0217-011). (\$ price only for South America) NOT FOR USA	679
AXIS 211M Outdoor T92A Kit	EOL	0269-041	387277	Bundle with 1 unit of AXIS 211M and AXIS T92A00 Housing (5015-001) aluminum outdoor housing. Including wall mount (0217-031). NOT FOR USA	799
AXIS 211W		0270-002	353404	Varifocal DC-iris lens. 1/4" progressive scan CMOS. Connects over wireless LAN (IEEE 802.11g) or wired Ethernet. Exchangeable antenna. Down to 0.75 lux. Up to VGA 640x480 resolution at full 30 fps frame rate. Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Two-way, full duplex audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes antenna, adjustable stand and power supply.	539
AXIS 211W 10-pack		0270-022	353404-10PK	AXIS 211W in 10-pack. Cannot be sold separately. Power supplies included	5 319

AXIS 211W Outdoor Verso Bundle with outdoor camera		0270-032	354726	Bundle with 1 unit of AXIS 211W and Verso outdoor housing (0217-001). Including wall mount (0217-031) and power supply (0217-011) and antenna (same as in 5500-311). (\$ price only for South America) NOT FOR USA	739
AXIS 221 Day & Night Network Camera		0221-002	307226	Varifocal DC-iris lens . 1/3" progressive scan CCD. Down to 0.65 lux in color. Auto day/night mode . Up to VGA 640x480 resolution at 45 frames per second . Motion JPEG and MPEG-4 . Video Motion Detection and I/O for alarm/event handling. Power over Ethernet . RS-232/485 for data and PTZ control. Includes adjustable stand and power supply.	949
AXIS 221 10-pack		0221-082	326624	AXIS 221 in 10-pack. Cannot be sold separately . Power supplies included.	9 399
AXIS 221 Barebone 10-pack		0221-052	#N/D!	AXIS 221 Barebone in 10-pack. Cannot be sold separately . Power supplies included.	8 989
AXIS 221 Outdoor Verso Kit		0221-101	323874	Bundle with 1 unit of AXIS 221 and Verso outdoor housing (0217-001). Including wall mount (0217-031) and power supply (0217-011).	1 079
AXIS 221 Outdoor T92A Kit		0221-121	362813	Bundle with 1 unit of AXIS 221 and AXIS T92A00 Housing (5015-001)aluminum outdoor housing. Including wall mount (0217-031). NOT FOR USA	1 169
AXIS 221 Outdoor T92A Night Kit		0221-131	381402	Bundle with 1 unit of AXIS 221 and AXIS T92A00 Housing (5015-001) aluminum outdoor housing and AXIS T90A21 IR-LED 50-100 DEG (5013-211). Including wall mount (0217-031). NOT FOR USA	1 499
AXIS 223M	EOL	0247-002	331496	2.0 Megapixel 1/2.7" CCD . Varifocal DC-iris Megapixel lens. Auto day/night mode . Up to 1600x1200 resolution . Up to 12 frames per second in 16:9. Simultaneous Motion JPEG and MPEG-4 . Video Motion Detection and I/O for alarm/event handling. Two-way audio AAC/G.711. Power over Ethernet . RS-232 & RS-485 for data. Includes power supply.	1 089
AXIS 223M 10-pack	EOL	0247-031	358851	AXIS 223M in 10-pack. Cannot be sold separately . No power supplies.	10 759
AXIS 223M Barebone 10 pack	EOL	0247-051	363935	AXIS 223M in Barebone 10-pack. Cannot be sold separately . No power supplies. No Lens	9 859
AXIS 223M Outdoor Verso Kit	EOL	0247-041	345362	Bundle with 1 unit of AXIS 223M and Verso outdoor housing (0217-001). Including wall mount (0217-031) and power supply (0217-011).	1 219
AXIs 223M Outdoor T92A Kit	EOL	0247-061	381904	Bundle with 1 unit of AXIS 223M and AXIS T92A00 Housing (5015-001) aluminum outdoor housing. Including wall mount (0217-031). NOT FOR USA	1 309
AXIS Q1755 50Hz		0303-001	382753	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode . Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG . Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet . Power supply not included.	1 299
AXIS Q1755 60Hz		0304-001	384633	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode . Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG . Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet . Power supply not included.	1 299
AXIS Q1755 50Hz with PoE midspan		0303-032	382770	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode . Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG . Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet . Power supply not included. Includes one-port Midspan .	1 349
AXIS Q1755 60Hz with PoE midspan		n/a	#N/D!	2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode . Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG . Video motion detection and active tampering alarm. Gatekeeper functionality. I/O for alarm/event handling. Two-way audio with audio detection alarm. Power over Ethernet . Power supply not included. Includes one-port Midspan .	1 349
AXIS Q1755 50Hz 10-pack/bulk		0303-021	382753-10PK	AXIS Q1755 50Hz in 10-pack. Cannot be sold separately as single packs . No midspan.	12 829
AXIS Q1755 60Hz 10-pack/bulk		0304-021	384633-10PK	AXIS Q1755 60Hz in 10-pack. Cannot be sold separately as single packs . No midspan.	12 829
AXIS Q1755 Outdoor T92A Kit		0303-042	392446	Bundle with 1 unit of AXIS Q1755 50 Hz (0303-001) and AXIS T92A00 Housing (5015-001) aluminum outdoor housing. Including Wall mount (0217-031). NOT FOR USA	1 519
AXIS Q1755-E 50HZ		0347-001	418237	Outdoor, IP66-rated, 2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode. Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG. Video motion detection and active tampering alarm. Gatekeeper functionality. Two-way audio. Arctic temperature control. Operation in -30°C to +50°C when powered by IEEE 802.3af midspan or -40°C to +50°C with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included.	1 499
AXIS Q1755-E 60HZ		0348-001	419192	Outdoor, IP66-rated, 2.0 Megapixel HDTV camera with 10x zoom, auto focus and day/night mode. Complying with SMPTE standards for HDTV 1080i and 720P. 25/30 in all resolutions in H.264 or Motion JPEG. Video motion detection and active tampering alarm. Gatekeeper functionality. Two-way audio. Arctic Temperature Control. Operation in -30 °C to 45 °C (-22 °F to 113 °F) when powered by IEEE 802.3af midspan or down to -40 °C (-40 °F) with AXIS T8123 High PoE Midspan. Includes a removable sunshield, wall bracket and 5-meter Ethernet cable. Midspan not included.	1 499

AXIS 209FD		0281-002	359718	Indoor camera, fixed lens. 1/4" high-quality progressive-scan CMOS sensor. Flat, discreet and tamper-resistant casing. Up to VGA 640x480 resolution at 30 frames per second. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and alarm/event handling. Power over Ethernet incl one-port Midspan.	339
AXIS 209FD 10 Pack		0281-021	359720	AXIS 209FD in 10-pack without Midspans. Cannot be sold separately.	3 249
AXIS 209MFD	EOL	0283-002	359722	Indoor camera, fixed lens. 1.3 megapixel 1/3" progressive-scan CMOS sensor. Flat, discreet and tamper-resistant casing. Up to 1280x1024 megapixel resolution at 12 frames per second. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and alarm/event handling. Power over Ethernet incl one-port Midspan.	419
AXIS 209MFD 10 Pack	EOL	0283-021	359724	AXIS 209MFD in 10-pack without Midspans. Cannot be sold separately	4 009
AXIS M3113-VE		0412-001	441852	Outdoor fixed dome in a flat, discreet and vandal-resistant casing with a weather shield. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Power over Ethernet. Includes lens tool, top cover tool and mounting adapter for surface cable mounting. Midspan not included.	339
AXIS M3113-VE NOCAP		0441-001	441853	Outdoor fixed dome in a flat, discreet and vandal-resistant casing without weather shield for ceiling mounting. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Power over Ethernet. Includes lens tool, top cover tool and mounting adapter for surface cable mounting. Midspan not included.	339
AXIS M3114-VE		0413-001	441854	Outdoor fixed dome in a flat, discreet and vandal-resistant casing with a weather shield. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Power over Ethernet. Includes lens tool, top cover tool and mounting adapter for surface cable mounting. Midspan not included.	419
AXIS M3114-VE NOCAP		0442-001	441855	Outdoor fixed dome in a flat, discreet and vandal-resistant casing without weather shield for ceiling mounting. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Power over Ethernet. Includes lens tool, top cover tool and mounting adapter for surface cable mounting. Midspan not included.	419
AXIS M3114-VE NOCAP 2MM		0450-001	452416	Outdoor fixed dome in a flat, discreet and vandal-resistant casing without weather shield for ceiling mounting. Fixed, wide-angle lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Power over Ethernet. Includes lens tool, top cover tool and mounting adapter for surface cable mounting. Midspan not included.	459
AXIS M3113-R		0330-001	414784	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged RJ-45 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	339
AXIS M3113-R BULK 10PCS		0330-021	414784-10PK	AXIS M3113-R in 10-pack/bulk. No midspans, no mounting adapters.	3 329
AXIS M3113-R BULK 50PCS		0330-031	414784-50PK	AXIS M3113-R in 50-pack/bulk. No midspans, no mounting adapters.	16 639
AXIS M3113-R M12		0358-001	414785	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged M12 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	339
AXIS M3113-R M12 BULK 10PCS		0358-021	414785-10PK	AXIS M3113-R M12 in 10-pack/bulk. No midspans, no mounting adapters.	3 329
AXIS M3113-R M12 BULK 50PCS		0358-031	414785-50PK	AXIS M3113-R M12 in 50-pack/bulk. No midspans, no mounting adapters.	16 639
AXIS M3114-R		0342-001	414786	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged RJ-45 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	419
AXIS M3114-R BULK 10PCS		0342-021	414786-10PK	AXIS M3114-R in 10-pack/bulk. No midspans, no mounting adapters.	4 119
AXIS M3114-R BULK 50PCS		0342-031	414786-50PK	AXIS M3114-R in 50-pack/bulk. No midspans, no mounting adapters.	20 579
AXIS M3114-R M12		0359-001	414787	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged M12 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	419
AXIS M3114-R M12 BULK 10PCS		0359-021	414787-10PK	AXIS M3114-R M12 in 10-pack/bulk. No midspans, no mounting adapters.	4 119
AXIS M3114-R M12 BULK 50PCS		0359-031	414787-50PK	AXIS M3114-R M12 in 50-pack/bulk. No midspans, no mounting adapters.	20 579

AXIS M3114-R M12 2MM		0448-001	452417	Fixed dome camera with rugged design, adapted for mobile video surveillance. Fixed, wide angle lens. Flat, discreet and tamper-resistant casing. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Rugged RJ-45 network connector, Power over Ethernet. Includes lens tool, top cover tool and mounting adapters. Midspan not included.	459
AXIS M3011		0284-002	382756	Ultra-discreet fixed dome camera for recessed mounting in drop ceilings. Fixed lens. 1/4" progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max VGA 640 x 480 resolution at 30 fps. MPEG-4 Part 2 also supported. Video motion detection. Power over Ethernet only , one-port midspan included.	309
AXIS M3011 10-pack/bulk		0284-021	382756-10PK	AXIS M3011 in 10-pack. Cannot be sold separately as single packs. NO Midspans	2 949
AXIS M3014		0285-002	395253	Ultra-discreet fixed dome camera for recessed mounting in drop ceilings. Fixed lens, progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. Video motion detection. Power over Ethernet, one-port midspan included.	389
AXIS M3014 10-pack/bulk		0285-021	395253-10PK	AXIS M3014 in 10-pack. Cannot be sold separately as single packs. NO Midspans	3 709
AXIS M3203		0336-001	416402	Fixed dome with discreet and tamper-resistant casing. Varifocal 2.8-10 mm lens with fixed iris. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	309
AXIS M3203 BULK 10PCS		0336-021	416402-10PK	AXIS M3203 in 10-pack. Clear transparent covers. Cannot be sold separately as single packs. No midspans.	3 059
AXIS M3203 SURVEILLANCE KIT		0336-041	421819	Bundle with 4 units of AXIS M3203 and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 299
AXIS M3203-V		0345-001	416403	Fixed dome with discreet and vandal-resistant casing. Varifocal 2.8-10 mm lens with fixed iris. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	339
AXIS M3203-V BULK 10PCS		0345-021	416403-10PK	AXIS M3203-V in 10-pack. Clear transparent covers. Cannot be sold separately as single packs. No midspans.	3 359
AXIS M3204		0337-001	416404	Fixed dome with discreet and tamper-resistant casing. Varifocal 2.8-10 mm lens with fixed iris. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	389
AXIS M3204 BULK 10PCS		0337-021	416404-10PK	AXIS M3204 in 10-pack. Clear transparent covers. Cannot be sold separately as single packs. No midspans.	3 859
AXIS M3204 SURVEILLANCE KIT		0337-041	421820	Bundle with 4 units of AXIS M3204 and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 599
AXIS M3204-V		0346-001	416405	Fixed dome with discreet and vandal-resistant casing. Varifocal 2.8-10 mm lens with fixed iris. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	419
AXIS M3204-V BULK 10PCS		0346-021	416405-10PK	AXIS M3204-V in 10-pack. Clear transparent covers. Cannot be sold separately as single packs. No midspans.	4 159
AXIS 216FD	EOL	0240-002	326616	Varifocal DC-iris lens. 1/4" high-quality progressive scan CMOS sensor. Fixed dome with discreet and tamper-resistant casing. Up to VGA 640x480 resolution at 30 frames per second. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Two-way audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes power supply.	549
AXIS 216 FD 10-Pack	EOL	0240-022	326618	AXIS 216FD in 10-pack. Cannot be sold separately. Power supplies included.	5 409
AXIS 216FD-V	EOL	0268-002	339624	Varifocal DC-iris lens. 1/4" high-quality progressive scan CMOS sensor. Fixed dome with vandal-resistant and compact indoor casing. Up to VGA 640x480 resolution at 30 frames per second. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Two-way audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes power supply.	579
AXIS 216FD-V 10 Pack-Bulk	EOL	0268-022	339624-10PK	AXIS 216FD-V in 10-pack. Cannot be sold separately. Power supplies included.	5 709
AXIS P3301		0290-002	375121	Fixed dome with discreet and tamper-resistant casing. Varifocal 2.8-10 mm lens. 1/4" progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max. VGA 640 x 480 resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone, and audio detection. I/O for alarm/event handling. Power over Ethernet. Includes power supply	459
AXIS P3301 10-pack:bulk		0290-021	381066	AXIS P3301 in 10-pack. Cannot be sold separately as single packs. No power supplies.	4 509

AXIS P3301-V		0292-002	378509	Fixed dome with discreet and vandal-resistant casing. Varifocal 2.8-10 mm lens. 1/4" progressive scan CMOS sensor. Multiple, individually configurable H.264 and Motion JPEG streams; max. VGA 640 x 480 resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone, and audio detection. I/O for alarm/event handling. Power over Ethernet. Includes power supply	489
AXIS P3301-V 10 pack/bulk		0292-021	381067	AXIS P3301-V in 10-pack. Cannot be sold separately as single packs. No power supplies.	4 809
AXIS 216 MFD	EOL	0278-002	351909	1.3 Megapixel 1/3" progressive scan CMOS sensor. Varifocal DC-iris lens. Fixed dome with discreet and tamper-resistant indoor casing. Simultaneous Motion JPEG and MPEG-4 in full megapixel 1280x1024 resolution. 12 frames per second in full resolution, 30 frames per second in partial scan 800x600. Video Motion Detection and I/O for alarm/event handling. Two-way audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes power supply.	639
AXIS 216 MFD 10 pack	EOL	0278-021	358052	AXIS 216MFD in 10-pack. Cannot be sold separately. No power supplies.	6 269
AXIS 216MFD-V	EOL	0279-002	351911	1.3 Megapixel 1/3" progressive scan CMOS sensor. Varifocal DC-iris lens. Fixed dome with vandal-resistant and compact indoor casing. Simultaneous Motion JPEG and MPEG-4 in full megapixel 1280x1024 resolution. 12 frames per second in full resolution, 30 frames per second in partial scan 800x600. Video Motion Detection and I/O for alarm/event handling. Two-way audio AAC/G.711 with built-in microphone. Power over Ethernet. Includes power supply.	669
AXIS 216MFD-V 10 pack	EOL	0279-021	368769	AXIS 216MFD-V in 10-pack. Cannot be sold separately. No power supplies.	6 569
AXIS P3304		0352-002	416406	Fixed dome with discreet and tamper-resistant casing. Varifocal 2.8-10 mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone, and audio detection. I/O for alarm/event handling. Power over Ethernet. Includes power supply.	539
AXIS P3304 BULK 10PCS		0352-021	416406-10PK	AXIS P3304 in 10-pack. Cannot be sold separately as single packs. No power supplies.	5 299
AXIS P3304-V		0353-002	416407	Fixed dome with discreet and vandal-resistant casing. Varifocal 2.8-10 mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1 MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone, and audio detection. I/O for alarm/event handling. Power over Ethernet. Includes power supply.	569
AXIS P3304-V BULK 10PCS		0353-021	416407-10PK	AXIS P3304-V in 10-pack. Cannot be sold separately as single packs. No power supplies.	5 599
AXIS 225FD	EOL	0243-002	322236	Varifocal DC-iris lens. 1/4" progressive scan CCD. Auto day/night mode. Fixed dome with discreet, vandal-resistant out-door proof IP66 casing with built-in heater and fan. Up to VGA 640x480 resolution at 30 fps frame rate. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Power over Ethernet. RS-485 for data. Includes cable gland and indoor power supply.	899
AXIS 225FD 22 mm	EOL	0243-062	364706	Varifocal 9-22 mm DC-iris lens. 1/4" progressive scan CCD. Auto day/night mode. Fixed dome with discreet, vandal-resistant out-door proof IP66 casing with built-in heater and fan. Up to VGA 640x480 resolution at 30 fps frame rate. Simultaneous Motion JPEG and MPEG-4. Video Motion Detection and I/O for alarm/event handling. Power over Ethernet. RS-485 for data. Includes cable gland and indoor power supply.	899
AXIS P3343 12mm		0307-031	395934	SVGA, day/night, fixed dome with discreet, tamper-resistant indoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection- I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	639
AXIS P3343 12mm 10-pack/bulk CLEAR		0307-041	395934-10PK	AXIS P3343 12mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	6 269
AXIS P3343 12mm 10-pack/bulk SMOKED		0307-051	402917	AXIS P3343 12mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	6 269
AXIS P3343 6mm		0307-001	395938	SVGA, day/night, fixed dome with discreet, tamper-resistant indoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection- I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	639
AXIS P3343 6mm 10-pack/bulk CLEAR		0307-021	402918	AXIS P3343 6mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	6 269
AXIS P3343 6mm 10-pack/bulk SMOKED		0307-061	402920	AXIS P3343 6mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	6 269

AXIS P3343-V 12mm		0308-031	395939	SVGA, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection- I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	669
AXIS P3343-V 12mm 10-pack/bulk CLEAR		0308-041	402922	AXIS P3343-V 12mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	6 559
AXIS P3343-V 12mm 10-pack/bulk SMOKED		0308-051	402930	AXIS P3343-V 12mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	6 559
AXIS P3343-V 6mm		0308-001	395941	SVGA, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection- I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	669
AXIS P3343-V 6mm 10-pack/bulk CLEAR		0308-021	402940	AXIS P3343-V 6mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	6 559
AXIS P3343-V 6mm 10-pack/bulk SMOKED		0308-061	402942	AXIS P3343-V 6mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	6 559
AXIS P3343-VE 12mm		0299-031	395942	SVGA, day/night, fixed dome with discreet vandal-resistant, IP66-rated outdoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio detection and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	799
AXIS P3343-VE 12mm 4-pack/bulk CLEAR		0299-041	402944	AXIS P3343-VE 12mm in 4-pack. Cannot be sold separately as single packs. Clear transparent cover only.	3 139
AXIS P3343-VE 12mm 4-pack/bulk SMOKED		0299-051	402946	AXIS P3343-VE 12mm in 4-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	3 139
AXIS P3343-VE 6mm		0299-001	395943	SVGA, day/night, fixed dome with discreet vandal-resistant, IP66-rated outdoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max SVGA resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio detection and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	799
AXIS P3343-VE 6mm 4-pack/bulk CLEAR		0299-021	402947	AXIS P3343-VE 6mm in 4-pack. Cannot be sold separately as single packs. Clear transparent cover only.	3 139
AXIS P3343-VE 6mm 4-pack/bulk SMOKED		0299-061	402949	AXIS P3343-VE 6mm in 4-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	3 139
AXIS P3344 12mm		0326-041	395944	HDTV, day/night, fixed dome with discreet tamper-resistant indoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	729
AXIS P3344 12mm 10-pack/bulk CLEAR		0326-051	402950	AXIS P3344 12mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	7 149
AXIS P3344 12mm 10-pack/bulk SMOKED		0326-061	402954	AXIS P3344 12mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	7 149
AXIS P3344 6mm		0326-001	395947	HDTV, day/night, fixed dome with discreet tamper-resistant indoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	729
AXIS P3344 6mm 10-pack/bulk CLEAR		0326-021	402958	AXIS P3344 6mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	7 149

AXIS P3344 6mm 10-pack/bulk SMOKED		0326-031	402961	AXIS P3344 6mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	7 149
AXIS P3344-V 12mm		0327-041	395951	HDTV, day/night, fixed dome with discreet vandal-resitant indoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	759
AXIS P3344-V 12mm 10-pack/bulk CLEAR		0327-051	402979	AXIS P3344-V 12mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	7 449
AXIS P3344-V 12mm 10-pack/bulk SMOKED		0327-061	402980	AXIS P3344-V 12mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	7 449
AXIS P3344-V 6mm		0327-001	395955	HDTV, day/night, fixed dome with discreet vandal-resitant indoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p or 1MP resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	759
AXIS P3344-V 6mm 10-pack/bulk CLEAR		0327-021	402981	AXIS P3344-V 6mm in 10-pack. Cannot be sold separately as single packs. Clear transparent cover only.	7 449
AXIS P3344-V 6mm 10-pack/bulk SMOKED		0327-031	402982	AXIS P3344-V 6mm in 10-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	7 449
AXIS P3344-VE 12mm		0325-041	395957	HDTV, day/night, fixed dome with vandal-resitant, IP66-rated outdoor casing. Varifocal 3.3-12 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio detection and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	889
AXIS P3344-VE 12mm 4-pack/bulk CLEAR		0325-051	402983	AXIS P3344-VE 12mm in 4-pack. Cannot be sold separately as single packs. Clear transparent cover only.	3 499
AXIS P3344-VE 12mm 4-pack/bulk SMOKED		0325-061	402984	AXIS P3344-VE 12mm in 4-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	3 499
AXIS P3344-VE 6mm		0325-001	395961	HDTV, day/night, fixed dome with vandal-resitant, IP66-rated outdoor casing. Varifocal 2.5-6 mm DC-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV resolution at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio detection and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	889
AXIS P3344-VE 6mm 4-pack/bulk CLEAR		0325-021	402985	AXIS P3344-VE 6mm in 4-pack. Cannot be sold separately as single packs. Clear transparent cover only.	3 499
AXIS P3344-VE 6mm 4-pack/bulk SMOKED		0325-031	402986	AXIS P3344-VE 6mm in 4-pack. Cannot be sold separately as single packs. Smoked transparent cover only.	3 499
AXIS P3346		0369-001	431731	3 MP, day/night fixed dome with discreet, tamper-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	799
AXIS P3346-V		0370-001	431732	3MP, day/night fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	829

AXIS P3346-VE		0371-001	431733	3MP, day/night fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 3MP resolution at 20 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	959
AXIS P3367-V		0406-001	448517	5MP, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	929
AXIS P3367-VE		0407-001	448518	5MP, day/night, fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	1 069
Pan/Tilt/Zoom Cameras					
AXIS 212 PTZ		0257-002	330785	Pan/tilt/zoom camera without moving parts. 3x zoom. 140 degrees pan and 105 degrees tilt. Up to VGA resolution at 30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O for alarm/event handling. Two-way Audio. Includes wall mount kit and power supply.	549
AXIS 212 PTZ 10 pack/bulk		0257-022	330787	AXIS 212 PTZ in 10 pack. Cannot be sold separately. Power supplies included.	5 449
AXIS 212 PTZ-V		0280-002	368526	Vandal resistant version of AXIS 212 PTZ. Pan/tilt/zoom camera without moving parts. 3x zoom. 140 degrees pan and 105 degrees tilt. Up to VGA resolution at 30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O for alarm/event handling. Two-way Audio. Includes wall mount kit and power supply.	599
AXIS 212 PTZ-V 10 pack/bulk		0280-022	368526-10PK	AXIS 212 PTZ-V in 10 pack. Cannot be sold separately. Power supplies included.	5 949
AXIS 214PTZ 50HZ		0245-002	322239	Pan/tilt/zoom (x18) camera. Auto-iris, automatic day/night, and auto-focus zoom lens. Up to 4CIF resolution at 30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O for alarm/event handling. Two-way Audio full duplex. Includes ceiling mount kit and power supply.	1 199
AXIS 214PTZ 60HZ		0246-002	322241	Pan/tilt/zoom (x18) camera. Auto-iris, automatic day/night, and auto-focus zoom lens. Up to 4CIF resolution at 30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O for alarm/event handling. Two-way Audio full duplex. Includes ceiling mount kit and power supply.	1 199
AXIS 215PTZ 50Hz	EOL replacement product AXIS P5512 50 HZ	0273-002	351616	Compact Pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and auto-focus zoom lens. Up to 4CIF resolution at 25/30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O connections for alarm/event handling. Two-way, full duplex audio. Includes power supply, mounting kit for hard and drop ceiling and transparent cover smoked and clear.	949
AXIS 215PTZ 60Hz	EOL-replacement product AXIS P5512 60 HZ	0274-002	400717	Compact Pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and auto-focus zoom lens. Up to 4CIF resolution at 25/30 fps frame rate. Simultaneous MPEG-4 and Motion JPEG. I/O connections for alarm/event handling. Two-way, full duplex audio. Includes power supply, mounting kit for hard and drop ceiling and transparent cover smoked and clear.	949
AXIS 215PTZ -E 50Hz	EOL-replacement product AXIS P5512-E 50HZ	0305-001	384638	Outdoor, IP66-rated pan/tilt/zoom camera including auto-iris, automatic day/night, and autofocus 12x zoom lens. Up to 4CIF resolution at 30/25 fps. Simultaneous MPEG-4 and Motion JPEG. Pre-mounted wall bracket, 5-meter power and Ethernet cables. 100 - 240 V AC power input. Clear dome bubble.	1 249
AXIS 215PTZ -E 60Hz	EOL - replacement product AXIS P5512-E 60HZ	0306-001	384639	Outdoor, IP66-rated pan/tilt/zoom camera including auto-iris, automatic day/night, and autofocus 12x zoom lens. Up to 4CIF resolution at 30/25 fps. Simultaneous MPEG-4 and Motion JPEG. Pre-mounted wall bracket, 5-meter power and Ethernet cables. 100 - 240 V AC power input. Clear dome bubble.	1 249
AXIS P5532 50HZ		0309-002	418240	PTZ camera with 29x optical zoom, D1 resolution (720x576) and IP51 classification. H.264 and Motion JPEG, Day & Night, WDR, EIS. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	1 599
AXIS P5532-E 50HZ		0311-002	421821	Outdoor ready PTZ camera with 29x optical zoom, D1 resolution (720x576), IP66 and NEMA 4X classification. H.264 and Motion JPEG, Day & Night, WDR, Electronic Imaging Stabilization. Includes High PoE midspan, smoked and clear dome covers. Mounting brackets are not included.	1 949
AXIS P5532 60HZ		0310-002	432514	PTZ camera with 29x optical zoom, D1 resolution (720x480) and IP51 classification. H.264 and Motion JPEG, Day & Night, WDR, EIS. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	1 599

AXIS P5532-E 60HZ		0312-002	429110	Outdoor ready PTZ camera with 29x optical zoom, D1 resolution (720x480), IP66 and NEMA 4X classification. H.264 and Motion JPEG, Day & Night, WDR, Electronic Imaging Stabilization. Includes High PoE midspan, smoked and clear dome covers. Mounting brackets are not included.	1 949
AXIS P5512 50HZ		0408-001	438977	Compact pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 25/30 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE (midspan not included), mounting kit for hard and drop ceiling and transparent cover smoked and clear. I/O connections for alarm/event handling. Two-way, full duplex audio requires multi connection cable (not included)	949
AXIS P5512 60HZ		0409-001	438978	Compact pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 25/30 fps frame rate. Simultaneous H.264 and Motion JPEG, standard IEEE 802.3af PoE (midspan not included), mounting kit for hard and drop ceiling and transparent cover smoked and clear. I/O connections for alarm/event handling. Two-way, full duplex audio requires multi connection cable (not included)	949
AXIS P5512-E 50HZ		0410-001	438979	Outdoor, IP66-rated pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 25/30 fps. Simultaneous H.264 and Motion JPEG. Power over Ethernet IEEE 802.3af, (midspan not included), clear and smoked dome bubble included. Brackets AXIS T91A are sold separately.	1 299
AXIS P5512-E 60HZ		0411-001	438980	Outdoor, IP66-rated pan/tilt/zoom (12x) camera including auto-iris, automatic day/night, and autofocus zoom lens. Up to 4CIF resolution at 25/30 fps. Simultaneous H.264 and Motion JPEG. Power over Ethernet IEEE 802.3af, (midspan not included), clear and smoked dome bubble included. Brackets AXIS T91A are sold separately.	1 299
AXIS P5522 50 Hz		0419-002	438564	PTZ camera with 18x optical zoom, D1 resolution (720x576) and IP51 classification in H.264 and Motion JPEG, Day & Night. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	1 299
AXIS P5522 60 Hz		0420-002	438565	PTZ camera with 18x optical zoom, D1 resolution (720x480) and IP51 classification in H.264 and Motion JPEG, Day & Night. Two way audio, four I/O and external power with multi-connector cable (not included) Includes High PoE midspan, smoked and clear dome covers, and mounting kit for hard and drop ceilings.	1 299
AXIS P5522-E 50 Hz		0421-002	438421	Outdoor PTZ camera with 18x zoom, D1 resolution (720x576) and IP66 classification in H.264 and Motion JPEG, Day & Night. Includes High PoE midspan, smoked and clear dome covers. Brackets are sold separately	1 649
AXIS P5522-E 60 Hz		0422-002	438422	Outdoor PTZ camera with 18x zoom, D1 resolution (720x480) and IP66 classification in H.264 and Motion JPEG, Day & Night. Includes High PoE midspan, smoked and clear dome covers. Brackets are sold separately	1 649
AXIS M5013		0398-001	438420	Ceiling-mount mini PTZ dome camera with SVGA resolution and 3x digital zoom. 800x600 @ 30fps in H.264 and Motion JPEG. IP51 protection against dust and water. Only PoE, midspan not included. Hard and soft ceiling mounting brackets included.	449
AXIS M5014		0399-001	438419	Ceiling-mount mini PTZ dome camera with HDTV 720p resolution, 16:9 format and 3x digital zoom. 1280x720 @ 30fps in H.264 and Motion JPEG. IP51 protection against dust and water. Only PoE, midspan not included. Hard and soft ceiling mounting brackets included.	549
AXIS P5534 50Hz		0313-002	408188	HDTV 720p compliant PTZ camera with 18x optical zoom for indoor use. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, two-way audio, I/O, IP51. Two way audio, four I/O and external power with multi-connector cable (not included) Includes HiPoE midspan, smoked and clear dome covers and mounting kit for hard and drop ceilings	1 849
AXIS P5534-E 50Hz		0315-002	421822	HDTV 720p compliant outdoor-ready, PTZ camera with 18x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper. Includes High PoE 30 W midspan, smoked and clear dome. Mounting brackets are not included.	2 199
AXIS P5534 60Hz		0314-002	432709	HDTV 720p compliant PTZ camera with 18x optical zoom for indoor use. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, two-way audio, I/O, IP51. Two way audio, four I/O and external power with multi-connector cable (not included) Includes HiPoE midspan, smoked and clear dome covers and mounting kit for hard and drop ceilings	1 849
AXIS P5534-E 60Hz		0316-002	429111	HDTV 720p compliant outdoor-ready, PTZ camera with 18x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper. Includes High PoE 30 W midspan, smoked and clear dome. Mounting brackets are not included.	2 199
Pan/Tilt/Zoom Dome Cameras					
AXIS 232 D+ DOME CAMERA 50Hz	EOL - Replacement product AXIS P5532	0252-001	328508	Auto iris auto focus zoom lens. 1/4" CCD. WDR. Down to 0.3 lux in color. Auto day/night mode. Continuous 360° rotation. >0° to -90° tilt range. Up to 4CIF resolution at 30 fps frame rate. Motion JPEG and MPEG-4. I/O for alarm/event handling. Includes hard and drop ceiling mount kit and power supply.	1 899

AXIS 232 D+ DOME CAMERA 60Hz	EOL - Replacement product AXIS P5532	0253-001	330026	Auto iris auto focus zoom lens. 1/4" CCD. WDR. Down to 0.3 lux in color. Auto day/night mode. Continuous 360° rotation. >0° to -90° tilt range. Up to 4CIF resolution at 30 fps frame rate. Motion JPEG and MPEG-4. I/O for alarm/event handling. Includes hard and drop ceiling mount kit and power supply.	1 899
AXIS 233D 50Hz		0265-001	345903	35x optical zoom dome camera with WDR and area zoom. Auto day/night mode down to 0.5 lux in color and 0,008 in night mode. Continuous 360° rotation and 180° tilt with E-flip. Progressive Scan 4CIF resolution at 30/25fps in MPEG-4 or Motion JPEG. Two-way audio, I/O for alarm/event handling. Includes hard and drop ceiling mount kit, smoked and clear transparent covers and power supply.	2 399
AXIS 233D 60Hz		0266-001	345639	35x optical zoom dome camera with WDR and area zoom. Auto day/night mode down to 0.5 lux in color and 0,008 in night mode. Continuous 360° rotation and 180° tilt with E-flip. Progressive Scan 4CIF resolution at 30/25fps in MPEG-4 or Motion JPEG. Two-way audio, I/O for alarm/event handling. Includes hard and drop ceiling mount kit, smoked and clear transparent covers and power supply.	2 399
AXIS Q6032 50HZ		0356-002	441856	IP52, PTZ dome camera with 35x optical zoom. WDR, EIS. Auto day/night mode down to 0.5 lux in color and 0.008 in night mode. Continuous 360° rotation and 180° tilt with E-flip. Progressive scan Extended D1 resolution (736x576) at 25 fps in H.264 and Motion JPEG. Auto-tracking, Tour Recording. Two way audio, four I/O and external power with multi-connector cable (not included) Includes smoked and clear transparent bubble mounting kit for hard and falls ceiling and High PoE midspan.	2 149
AXIS Q6032-E 50 Hz		0317-002	395254	Outdoor-ready, IP66 and NEMA4X-rated, PTZ Dome camera with 35x optical zoom. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. WDR, EIS. Auto day/night mode down to 0.5 lux in color and 0.008 in night mode. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan 4CIF resolution @ 25 fps in H.264 and Motion JPEG. Auto-tracking. Power through High PoE only. Includes clear transparent bubble and High PoE midspan. No mounting bracket included (several different available as accessories).	2 699
AXIS Q6032 60HZ			#N/D!	IP52, PTZ dome camera with 35x optical zoom. WDR, EIS. Auto day/night mode down to 0.5 lux in color and 0.008 in night mode. Continuous 360° rotation and 180° tilt with E-flip. Progressive scan Extended D1 resolution (752x480) at 30fps in H.264 and Motion JPEG. Auto-tracking, Tour Recording. Two way audio, four I/O and external power with multi-connector cable (not included) Includes smoked and clear transparent bubble mounting kit for hard and falls ceiling and High PoE midspan.	2 149
AXIS Q6032-E 60 Hz		n/a	#N/D!	Outdoor-ready, IP66 and NEMA4X-rated, PTZ Dome camera with 35x optical zoom. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. WDR, EIS. Auto day/night mode down to 0.5 lux in color and 0.008 in night mode. Continuous 360° rotation and 220° tilt with E-flip. Progressive scan 4CIF resolution @ 25 fps in H.264 and Motion JPEG. Auto-tracking. Power through High PoE only. Includes clear transparent bubble and High PoE midspan. No mounting bracket included (several different available as accessories).	2 699
AXIS Q6034 60HZ		0363-004	419667	HDTV 720p compliant high speed PTZ Dome camera with 18x optical zoom for indoor use. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP52. Two way audio, four I/O and external power with multi-connector cable (not included) Includes Hi PoE midspan, smoked and clear dome covers and mounting kit for hard and drop ceilings.	2 399
AXIS Q6034 50HZ		0331-002	419676	HDTV 720p compliant high speed PTZ Dome camera with 18x optical zoom for indoor use. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP52. Two way audio, four I/O and external power with multi-connector cable (not included) Includes Hi PoE midspan, smoked and clear dome covers and mounting kit for hard and drop ceilings.	2 399
AXIS Q6034-E 50HZ		0355-002	421823	Top performance HDTV 720p compliant Outdoor ready, high speed PTZ camera with 18x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. Active Gate Kepeer and autotracking. Includes Hi PoE midspan, clear dome. Mounting brackets are not included	2 949
AXIS Q6034-E 60HZ		n/a	#N/D!	Top performance HDTV 720p compliant Outdoor ready, high speed PTZ camera with 18x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66 and NEMA 4X. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. Active Gate Kepeer and autotracking. Includes Hi PoE midspan, clear dome. Mounting brackets are not included	2 949
AXIS Q6035 50HZ		0429-002	441857	HDTV 1080p compliant high speed PTZ dome camera with 20x optical zoom for indoor use. Continuous 360° rotation. HDTV 1080p (1920x1080) @ 25/30 fps, HDTV 720p @ 50/60 fps in H.264, Day & Night, WDR, IP52. Two-way audio, I/O and external power with multi-connector cable (not included). Smoked and clear dome covers, mounting kit for hard and drop ceiling, and midspan are included.	2 899
AXIS Q6035 60HZ			#N/D!	HDTV 1080p compliant high speed PTZ dome camera with 20x optical zoom for indoor use. Continuous 360° rotation. HDTV 1080p (1920x1080) @ 25 fps, HDTV 720p @ 50/60 fps in H.264, Day & Night, WDR, IP52. Two-way audio, I/O and external power with multi-connector cable (not included). Smoked and clear dome covers, mounting kit for hard and drop ceiling, and midspan are included.	2 899
AXIS Q6035-E 50HZ		0430-002	441858	HDTV 1080p compliant outdoor-ready, IP66 and NEMA 4X-rated, PTZ dome camera with 20x optical zoom. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. WDR. Auto day/night mode. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 25 fps, HDTV 720p @ 50 fps in H.264. Auto-tracking. Power through High PoE only. Clear transparent dome cover and High PoE midspan are included. Brackets are not included	3 449

AXIS Q6035-E 60 HZ			#N/D!	HDTV 1080p compliant outdoor-ready, IP66 and NEMA 4X-rated, PTZ dome camera with 20x optical zoom. Arctic Temperature Control enables operation and start up from -40 °C to +50 °C. WDR. Auto day/night mode. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps, HDTV 720p @ 60 fps in H.264. Auto-tracking. Power through High PoE only. Clear transparent dome cover and High PoE midspan are included. Brackets are not included	3 449
Special Cameras					
AXIS P8513 WHITE (CM DECAL)	NEW	0451-001	454470	White eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. SVGA resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	799
AXIS P8513 BLACK (CM DECAL)	NEW	0452-001	454471	Black eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with optional height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. SVGA resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	799
AXIS P8513 CHROME (CM DECAL)	NEW	0453-001	454472	Chrome eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with optional height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. SVGA resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	799
AXIS P8514 CHROME (CM DECAL)	NEW	0456-001	454473	Chrome eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with optional height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	879
AXIS P8514 BLACK (CM DECAL)	NEW	0455-001	454474	Black eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with optional height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	879
AXIS P8514 WHITE (CM DECAL)	NEW	0454-001	454475	White eye-level camera for face identification. Covertly pre-installed at a height of 160cm (5.2 ft.)in a steel pipe with height indicator decal, it offers a subtle indoor video surveillance that blends in with any retail, hotel and banking environment. HDTV 720p resolution at 30 fps, fixed focal pinhole lens, multiple, individually configurable H.264 and Motion JPEG streams, video motion detection and active tampering alarm. Power over Ethernet, pre-mounted 130cm (4.3 ft.)Ethernet cable with female RJ45 connector	879
Thermal Cameras					
AXIS Q1910		0334-001	413363	Indoor Thermal Network Camera, 160x128 resolution, 8.33 fps, and 17° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	2 229
AXIS Q1910-E		0335-001	413364	Outdoor ready Thermal Network Camera, IP66-rated, 160x128 resolution, 8.33 fps, and 17° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	2 599
AXIS Q1921 19MM 30FPS		0384-001	429112	Indoor Thermal Network Camera, 384x288 resolution, 30 fps, and 29° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 599
AXIS Q1921 10MM 30FPS		0388-001	429113	Indoor Thermal Network Camera, 384x288 resolution, 30 fps, and 55° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 599
AXIS Q1921-E 10MM 30FPS		0389-001	429114	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 30 fps, and 55° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 999
AXIS Q1921-E 19MM 30FPS		0385-001	429115	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 30 fps, and 29° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 999
AXIS Q1921-E 35MM 30FPS		0390-001	429116	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 30 fps, and 15° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	4 749

AXIS Q1921-E 60MM 30FPS	8-week lead time	0391-001	429117	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 30 fps, and 9° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	6 699
AXIS Q1921 19MM 8.3 fps		0400-001	430059	Indoor Thermal Network Camera, 384x288 resolution, 8.33 fps, and 29° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 599
AXIS Q1921-E 19MM 8.3 fps		0401-001	430060	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 8.33 fps, and 29° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 999
AXIS Q1921 10MM 8.3 fps		0402-001	430061	Indoor Thermal Network Camera, 384x288 resolution, 8.33 fps, and 55° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 599
AXIS Q1921-E 10MM 8.3 fps		0403-001	430062	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 8.33 fps, and 55° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	3 999
AXIS Q1921-E 35MM 8.3 fps		0404-001	430063	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 8.33 fps, and 15° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	4 749
AXIS Q1921-E 60MM 8.3 fps		0405-001	430064	Outdoor ready Thermal Network Camera, IP66-rated, 384x288 resolution, 8.33 fps, and 9° angle of view. It supports ONVIF, PT heads, H.264, audio, local storage, I/O, PoE, tampering alarm, motion detection, and AXIS Camera Application Platform.	6 699
VIDEO ENCODERS					
1-port Video Encoders					
AXIS 241S		0186-002	277642	1 channel NTSC/PAL video encoder. Motion JPEG and MPEG-4. Up to 30/25 fps. I/O for alarm/event handling. RS-232/RS-485 for data and PTZ control.	449
AXIS 241S 10-Pack		0186-022	319829	AXIS 241S in 10-pack. Cannot be sold separately. Power supplies included.	4 359
AXIS 241S Blade		0210-001	286484	Blade version of AXIS 241S.	359
AXIS 241S Blade 10-pack		0210-021	286485	Blade version of AXIS 241S in 10-pack. Cannot be sold separately	3 459
AXIS 243SA		0256-002	343254	One channel, high quality full frame rate video up to 25/30 fps in all resolutions , in MPEG-4 as well as Motion JPEG. Support for simultaneous MPEG-4 and Motion JPEG streams. Two-way audio , motion detection, remote pan/tilt/zoom control and security package including HTTPS encryption.	629
AXIS 243SA 10-pack/bulk		0256-022	378511	AXIS 243SA in 10-pack. Cannot be sold separately. Power supplies included.	6 099
AXIS 247S		0272-001	347818	1 channel , high quality video up to 30/25 fps in all resolutions. Simultaneous Motion JPEG and MPEG-4. One-way audio , motion detection and security package including HTTPS encryption. Powered over Ethernet (IEEE 802.3af) with power out for the analog camera. No power supply included.	449
AXIS 247S 10 pack/bul		0272-021	347818-10PK	AXIS 247S in 10-pack. Cannot be sold separately. No power supplies.	4 359
Axis 282		0237-001	336939	Bare board 1 channel video server for built-in purposes. Small footprint unit for flexible integration. Motion JPEG and MPEG-4. Up to 30/25 fps. I/O for alarm/event handling. RS-232 or RS-485 for data and PTZ control.	449
AXIS 282 20-pack/bulk		0237-011	323633	AXIS 282 in 20-pack. Cannot be sold separately. No power supplies.	8 639
AXIS 282A		0238-001	336940	Bare board 1 channel video server with duplex audio for built-in purposes. Small footprint unit for flexible integration. Motion JPEG and MPEG-4. Up to 30/25 fps. I/O for alarm/event handling. RS-232 or RS-485 for data and PTZ control.	499
AXIS 282A 20-pack/bulk		0238-011	#N/D!	AXIS 282A in 20-pack. Cannot be sold separately. No power supplies.	9 519
AXIS M7001		0298-001	386513	1-channel video encoder. Dual streaming in H.264 and Motion JPEG; max. D1 resolution at 30/25 fps. Video motion detection. Power over Ethernet (IEEE 802.3af) only. NO midspan	249
AXIS M7001 10-pack/bulk		0298-021	386513-10PK	AXIS M7001 in 10-pack/bulk. Cannot be sold separately as single packs. NO midspans	2 419
AXIS M7001 Covert Surveillance Kit		0298-031	387051	1-channel video encoder together with a small IP66 covert camera. Dual streaming in H.264 and Motion JPEG; max. D1 resolution at 30/25 fps. Video motion detection. Power over Ethernet (IEEE 802.3af) only with power out for the covert camera. NO midspan	329
AXIS M7001 Covert Surveillance Kit 10-pack/bulk		0298-041	387051-10PK	AXIS M7001 Covert Surveillance Kit in 10-pack/bulk. Cannot be sold separately as single packs. NO midspans	3 189
AXIS M7014	NEW	0415-002	448180	Four-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 15 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC card. PTZ support. Includes power supply.	399
AXIS M7014 SURVEILLANCE KIT	NEW	0415-042	452418	Bundle with 1 unit of AXIS M7014 Video Encoder and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	449

AXIS M7010	NEW	0414-002	448179	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 15 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC cards. PTZ support. Includes power supply.	1 599
AXIS M7010 SURVEILLANCE KIT	NEW	0414-042	452419	Bundle with 1 unit of AXIS M7010 Video Encoder and a 16-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	1 749
AXIS P7214	NEW	0417-002	448182	Four-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC card. PTZ support. Includes power supply.	559
AXIS P7214 SURVEILLANCE KIT	NEW	0417-042	#N/D!	Bundle with 1 unit of AXIS P7214 Video Encoder and a 4-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	599
AXIS P7224 Video Encoder Blade	NEW	0418-001	452420	Four-channel video encoder blade. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. PTZ support. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	559
AXIS P7224 VID ENC BLADE BULK 10PCS	NEW	0418-021	#N/D!	AXIS P7214 in 10-pack. Cannot be sold separately as single packs.	5 440
AXIS P7210	NEW	0416-002	448181	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. Power over Ethernet (IEEE 802.3af). Local storage using microSDHC cards. PTZ support. Includes power supply.	1 999
AXIS P7210 SURVEILLANCE KIT	NEW	0416-042	#N/D!	Bundle with 1 unit of AXIS P7010 Video Encoder and a 16-camera base license of AXIS Camera Station video management software for monitoring, recording, playback and event management. Kits can be scaled and combined to build a truly effective and reliable surveillance solution for any system size up to 50 cameras. To meet any specific need additional cameras and AXIS Camera Station upgrade licenses can be ordered separately.	2 149
AXIS Q7401		0288-002	376918	1 channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection. Power over Ethernet (IEEE 802.3af) with power out for the analog camera. SD/SDHC memory card slot for local storage. Includes power supply.	499
AXIS Q7401 VIDEO ENCODER BULK 10PCS		0288-021	#N/D!	AXIS Q7401 in 10-pack. Cannot be sold separately as single pack. Without power supplies.	4 839
AXIS Q7401 VIDEO ENCODER BARE BONE		0288-041	#N/D!	Bare board 1 channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection. Power over Ethernet (IEEE 802.3af) with power out for the analog camera. SD/SDHC memory card slot for local storage.. No power supply.	499
AXIS Q7401 VIDEO ENCODER BARE BONE BULK 20PCS		0288-051	418614	AXIS Q7401 BARE BONE in 20-pack. Cannot be sold separately as single packs. No power supplies.	9 980
AXIS P8221		0321-002	404618	Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two-way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	299
AXIS P8221 10-pack/bulk		0321-021	404618-10PK	AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	2 949
4-port Video Encoders					
AXIS 240Q	EOL - Replacement product AXIS M7014	0232-002	318750	4 channel NTSC/PAL video encoder. Motion JPEG. Up to 24/20 total fps. I/O for alarm/event handling. RS-232/RS-485 for data and PTZ control.	449
AXIS 240Q 10 pack	EOL - Replacement product AXIS M7014	0232-052	324587	AXIS 240Q in 10-pack. Cannot be sold separately. Power supplies included.	4 359
AXIS 240Q Blade	EOL - Replacement product AXIS P7224	0232-021	334767	Blade version of AXIS 240Q.	359
AXIS 240Q Blade 10 pack	EOL - Replacement product AXIS P7224	0232-081	364433	Blade version of AXIS 240Q in 10-pack. Cannot be sold separately	3 459

AXIS 241Q		0185-002	271054	4 channel NTSC/PAL video encoder. Motion JPEG and MPEG-4. Up to 120/100 total fps. I/O for alarm/event handling. RS-232/RS-485 for data and PTZ control.	719
AXIS 241Q 10-Pack		0185-022	324588	AXIS 241Q in 10-pack. Cannot be sold separately. Power supplies included.	6 959
AXIS 241Q Blade		0209-001	286482	Blade version of AXIS 241Q.	629
AXIS 241Q Blade 10-pack		0209-021	286483	Blade version of AXIS 241Q in 10-pack. Cannot be sold separately	6 059
AXIS 241QA		0230-002	316153	4 channel NTSC/PAL video encoder with duplex audio. Motion JPEG and MPEG-4. Up to 120/100 total fps. I/O for alarm/event handling. RS-232/RS-485 for data and PTZ control.	759
AXIS 241QA 10 pack		0230-022	#N/D!	AXIS 241QA in 10-pack. Cannot be sold separately. Power supplies included.	7 319
AXIS 243Q Blade		0261-001	RIM-341548	4 channel Blade Server, high quality full frame rate video up to 25/30 fps in all resolutions, in MPEG-4 or Motion JPEG. Support for simultaneous MPEG-4 and Motion JPEG streams, motion detection, remote pan/tilt/zoom control and security package including HTTPS encryption. ONLY COMPATIBLE WITH AXIS 291 1U VIDEO SERVER RACK	899
AXIS 243Q Blade 10 pack-bulk		0261-021	353226	AXIS 243Q blade in 10-pack. Cannot be sold separately	8 699
AXIS Q7404		0291-002	395255	Four-channel video encoder. Multiple, individually configurable H.264 and Motion JPEG streams per channel; max. D1 resolution at 30/25 (NTSC/PAL) fps. Video motion detection. Active tampering alarm. Two-way audio and audio detection on one channel. PTZ support. Includes power supply.	899
AXIS Q7404 10-pack/bulk		0291-022	395255-10PK	AXIS Q7404 in 10-pack. Cannot be sold separately as single packs. Power supplies included.	8 719
AXIS Q7414 VIDEO ENCODER BLADE		0354-001	443948	Four channel video encoder blade. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps per channel. Four bi-directional audio channels with AAC encoding. Video motion detection. Active tampering alarm. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	959
AXIS Q7414 VIDEO ENCODER BULK 10PCS		0354-021	#N/D!	AXIS Q7414 in 10-pack. Cannot be sold separately as single packs.	9 390
6-port Video Encoders					
AXIS Q7406		0289-001	376917	6 channel video encoder blade. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps per channel. Video motion detection. Active tampering alarm. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK	1 159
12-port Video Encoders					
AXIS 12 Channel Video Server Bundle		0277-002	348914	3 x AXIS 243Q Blade mounted in an AXIS 291 1U Rack.	2 999
AXIS 12 Channel Video Server Bundle Generic		0277-001	#N/D!	3 x AXIS 243Q Blade mounted in an AXIS 291 1U Rack. No power cable.	2 999
AXIS 18 Channel Video Encoder Bundle		0322-002	390055	3 x AXIS Q7406 Blade mounted in an AXIS 291 1U Rack. Country specific power cable.	3 759
AXIS 84 Channel Video Encoder Bundle		0323-002	390057	14 x AXIS Q7406 Blade mounted in an AXIS Q7900 Rack. Country specific power cable.	18 999
1-port Video Decoder					
AXIS P7701		0319-002	413365	1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G.726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. Includes power supply.	359
AXIS P7701 VIDEO DECODER BARE BONE		0319-041	428835	Bare board 1 channel video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G.726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	359
AXIS P7701 VIDEO DEC BB BULK 20PCS		0319-051	428835-20PK	AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	7 180
Blade Video Server Rack					
AXIS Video Server Rack		0192-002	286480	Rack unit for AXIS Blade video servers. 19". Will hold up to 12 Blade video servers. Comes complete with integrated power supply and blanking panels.	1 199
AXIS 291 1U Video Server Rack		0267-002	344992	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	349
AXIS 291 1U Video Server Rack Generic		0267-001	#N/D!	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output. No power cable.	349
AXIS Q7900 Rack		0287-002	376916	4U 19" rack with 14 slots for Axis video encoder blades. Supports up to 84 analog channels. Multiple video streams per channel through four Gigabit Ethernet ports. Two redundant power supply units. Each slot offers six RS-485 connectors for PTZ control and 12 I/O ports for connections to external devices. Compatible with all current Axis video encoder blades	3149
RECORDING SOLUTIONS					
Application Software					
AXIS Camera Station					
AXIS Camera Station Base Pack 4 channels EN		0202-052	310919	In English. Versatile IP surveillance software for recording and viewing live video remotely. Record continuously, on alarm or when motion is detected with instant playback of recorded images. Base pack with a license for 4 Axis network video channels. Includes a 1 year free software upgrade right. Delivered in a box with CD-ROM and QIG.	599
AXIS Camera Station Base Pack 10 channels EN		0202-002	279039	In English. Versatile IP surveillance software for recording and viewing live video remotely. Record continuously, on alarm or when motion is detected with instant playback of recorded images. Base pack with a license for 10 Axis network video channels. Includes a 1 year free software upgrade right. Delivered in a box with CD-ROM and QIG.	899

AXIS Camera Station 1 channel Upgrade English and Multilingual		0202-032	288730	License for 1 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	89
AXIS Camera Station 5 channels Upgrade English and Multilingual		0202-012	288729	License for 5 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	445
AXIS Camera Station 20 license add-on		0202-262	380781	License for 20 additional Axis network video channel to AXIS Camera Station 4 or 10 license base pack. Requires the base pack to be pre-installed. Delivered as a license code in an envelope.	1 779
AXIS Camera Station 1 year support extension		0202-022	288731	Adds a 1 year free support and software upgrade right to the 1 year period included in the AXIS Camera Station 4 or 10 license base pack.	109
AXIS Camera Management					
AXIS Camera Management			#N/D!	Powerful and efficient installation and management tool for Axis network video products. The tool can automatically find and set IP addresses , configure, show connection status and manage firmware upgrades of multiple devices .	Free Download
AXIS Mobile Monitor					
AXIS Mobile Monitor			#N/D!	AXIS Mobile Monitor enables quick and easy access to live video from Axis network video products, directly on smartphones or Pocket PCs. It provides pan/tilt/zoom operation and manual control of I/O ports.	Free Download
AXIS Installation Monitor					
AXIS Installation Monitor			#N/D!	The AXIS Installation Monitor gives installers a tool that simplifies the physical installation and service of Axis wired and wireless network cameras. Using a handheld Pocket PC computer, the installer can view the live images , and adjust focus, angle and direction without using a laptop or a colleague at a computer elsewhere.	Free Download
AXIS MPEG Decoder Licence					
AXIS MPEG-4 Decoder 50-user licence pack		0160-030	358870	A license document that grants installation of AXIS MPEG-4 decoder onto 50 separate computers . Applicable for all Axis MPEG-4 products that does not support AAC audio encoding. (e.g. models: 210, 211, 210A, 211A, 213, 214, 221, 225FD, 231D+, 232D+, 241S, 241Q, 241SA, 241QA, 242SIV, 243SA, 282, 282A)	45
AXIS MPEG-4 +AAC decoder 50-user license		0160-040	352755	A license document that grants installation of AXIS MPEG-4 and AAC decoder onto 50 separate computers . Applicable for all Axis products that supports MPEG-4. Required for models that supports AAC audio encoding (e.g. models: 207, 207W, 207MW, 212PTZ, 216FD, 223M)	65
AXIS H. 264 50-user decoder license pack		0160-050	390849	A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	30
AXIS H.264 +AAC decoder 50-user decoder license pack		0160-060	378892	A license document that grants installation of AXIS AVC/H.264 and ACC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	39
AXIS Camera Application Platform					
Axis Cross Line Detection		0333-011	408196	License code that grants installation of Axis Cross Line Detection application on one camera/encoder. Visit www.axis.com for supported cameras/encoders products and download of the application.	25
Axis Cross Line Detection 10-pack		0333-031	408196-10PK	License code that grants installation of Axis Cross Line Detection application on up to 10 cameras/encoders. Visit www.axis.com for supported cameras/encoders products and download of the application.	239
Axis Cross Line Detection 50-pack		0333-051	408196-50PK	License code that grants installation of Axis Cross Line Detection application on up to 50 cameras/encoders. Visit www.axis.com for supported cameras/encoders products and download of the application.	1 169
Network Video Recorder					
AXIS Q8108-R		0332-031	418242	8-channel network video recorder (NVR) developed to withstand shocks, vibrations and temperature fluctuations in public and commercial transportation applications. AXIS Q8108-R provides uninterrupted in-vehicle recording also in full frame rate HDTV resolution and offers an integrated 8-port PoE switch for easy and cost efficient installation. Hard disks not included.	3 049
ACCESSORIES					
PTZ/PTZ dome accessories					
AXIS T91A61 Wall Bracket		5017-611	395265	Wall Bracket. For use with AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. Includes mounting plate. White.	79
AXIS T91A62 BRACKET PARAPET		5017-621	418104	Parapet Bracket. For use with AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. 67 x 36 cm / 26 x 14 inch. White.	149
AXIS T91A63 Ceiling Bracket		5017-631	404887	Ceiling Bracket. 70 cm / 28 inch. For use with AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	99
AXIS T91A67 Pole Bracket		5017-671	395267	Pole Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. Includes steel pole straps. White. Requires mounting tool Part no: 21776	79

AXIS T91A64 Corner Bracket		5017-641	395268	Corner Bracket. Requires AXIS T91A61 Wall Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	59
AXIS Q6032-E Pendant Kit		5502-431	395269	With AXIS Q6032-E PENDANT KIT it is possible to mount the AXIS Q6032-E PTZ Dome Network Camera and AXIS P5534 PTZ Network Camera on standard '1.5" NPT threaded brackets. White.	44
Axis 295 Video Surveillance Joystick	EOL	0248-001	327929	Professional joystick for accurate control over network of all Axis pan/tilt/zoom and dome network cameras. Connects to PC workstation over USB. Features a three-axis Hall Effect joystick with X/Y-axis for positioning and turning knob for zoom, and twelve programmable push-buttons. NOTE! The joystick will not be supported in the web interface of 213, 214 and 23xD cameras until the 4.40 FW version released during Q2 2006.	299
AXIS T8310 CONTROL BOARD		5020-001	416408	Modular control board for professional camera and video management. AXIS T8310 Control Board is a complete control board solution which includes AXIS T8311 Joystick, AXIS T8312 Keypad and AXIS T8313 Jog Dial. Includes required USB cables inter-connecting the units and a 2 meter USB cable to the workstation. AXIS T8310 Video Surveillance Control Board is supported in ACS ver. 3.3 or later.	899
AXIS T8311 JOYSTICK		5020-101	416409	Professional joystick for accurate control of Axis pan/tilt/zoom and dome network cameras. Connects to the workstation over USB. Features a three-axis joystick with X/Y-axis for positioning and turning knob for zoom and 6 push-buttons. Includes a 2 meter USB cable for connection to the workstation. AXIS T8311 Joystick is supported in ACS ver. 3.3 or later.	349
AXIS T8312 KEYPAD		5020-201	416411	Professional 22 button keypad for quick navigation between workspaces, camera views and PTZ. Connects to the workstation over USB. Includes a 2 meter USB cable for connection to the workstation. AXIS T8312 Keypad is supported in ACS ver. 3.3 or later.	349
AXIS T8313 JOG DIAL		5020-301	416412	Professional video surveillance jog dial for high precision playback, facilitating functions such as play, pause, index, image steps and fast search. 6 built-in push buttons additionally simplifies video forensics. AXIS T8313 Jog Dial is supported in ACS ver. 3.3 or later.	299
ACC BRACKET OUTDOOR AXIS 233D		5500-471	354197	AXIS 233D mounting bracket for Video Alarm and Video Techs outdoor housing that are designed for AXIS 231/232D	35
CABLE RJ45 OUTDOOR 5M		5502-731	420099	Outdoor CAT6 ethernet cable. IP66 rated male push pull connector for for AXIS Q6032-E, IP20 rated male RJ45 connector for midspan. Length 5 meters. Color black.	59
Junction box for AXIS 231D/232D		21781	316061	Indoor junction box (included with AXIS 213D/232D), available as spare part	71
Junction cable for AXIS 231D/232D 1m		21786	316066	Cable between AXIS 231D/232D and junction box, optional accessory. 1m.	14
Junction cable for AXIS 231D/232D 2m		21787	316067	Cable between AXIS 231D/232D and junction box, optional accessory. 2m.	17
Junction cable for AXIS 231D/232D 5m		21788	316068	Cable between AXIS 231D/232D and junction box, optional accessory. 5m.	25
Junction cable for AXIS 231D/232D 10m		21789	316069	Cable between AXIS 231D/232D and junction box, optional accessory. 10m.	42
Cable AXIS 233D I/O Outdoor		28256	351913	Cable for I/O outdoor. 3,5 meter	20
ACC CABLE I/O AUDIO 5M P553X		5502-491	416105	Multi-connector cable for power, audio and I/O. Used for AXIS P5534 PTZ Dome Network Camera.	99
ACC Wall Mount AXIS PS24		5000-011	323624	Metal box to mount AXIS PS24 to a wall.	45
Pole Mount, Wide 231/232D		21764	316047	Out door pole mount, for use with AXIS PS24 Wall mount (5000-011)	48
Mounting Tool for pole mounts 231/232D		21776	316058	Tool for steel strap tensioning. For use with 21764 and AXIS T91A67	116
Cable 1m for AXIS 231/232D outdoor housing		21782	316062	Outdoor cable - for connecting power supply and outdoor housing	10
Cable 2m for AXIS 231/232D outdoor housing		21783	316063	Outdoor cable - for connecting power supply and outdoor housing	12
Cable 5m for AXIS 231/232D outdoor housing		21784	316064	Outdoor cable - for connecting power supply and outdoor housing	20
Cable 10m for AXIS 231/232D outdoor housing		21785	316065	Outdoor cable - for connecting power supply and outdoor housing	35
AXIS 213CM Connection Module	EOL	22581	286168	Connection module for the AXIS 213 PTZ Network Camera. Provides two way, full duplex audio functionality, analog video out (for ceiling mounted camera), 2 alarm inputs and 3 outputs for the AXIS 213 PTZ. Cable included.	89
AXIS 213 WALL BRACKET		5500-071	336093	AXIS 213 WALL BRACKET allows mounting the AXIS 213 PTZ Network Camera on a wall, or other vertical surface.	39
ACC Mount Bracket down AXIS 212PTZ-V		5500-791	365679	AXIS 212PTZ-V vertical tilt mount bracket. For AXIS 212PTZ network cameras. Powder coated aluminum. 37.7 degree downward angle.	44
Videotec Dome Housing Trans DBH24K0F028	EOL	0216-001	288915	Dome housing for Axis 213/214 PTZ Network Camera and Axis 231D/231D+/232D/232D+/233D Network Dome Camera with clear bubble. Color: White	279
Videotec Dome Housing Smoked DBH24K0F022	EOL	0216-011	288248	Dome housing for AXIS 213/214 PTZ Network Camera and Axis 231D/231D+/232D/232D+/233D Network Dome Camera with smoked bubble. Color: White	279
Videotec Dome House Adapt 213 ODBH24H144	EOL	0216-021	288249	Adapter for Axis 213 For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Other: With 230VAC heater /w fan	129
Videotec Dome House Adapt 214 ODBH24H151	EOL	0216-111	334885	Adapter for AXIS 214 For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Other: With 230VAC heater /w fan	149

Videotec Dome House Adapt 215 ODBH24H144	EOL	0216-121	360169	Adapter for AXIS 215 For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Other: With 230VAC heater /w fan	139
Videotec Dome House Ceiling Mount DBH03	EOL	0216-031	383789	Ceiling mount For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Color: Black	115
Videotec Dome House Wall Mount DBH04		0216-041	288250	Wall mount For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Color: Black	99
Videotec Dome House Parapet Mount DBH05		0216-051	370465	Parapet mount For use with: Videotec DBH24K0F022, DBH24K0F028 (Axis 0216-001, Axis 0216-011) Color: Black	229
Videotec Dome House Pole Adapter DPTCH		0216-061	310324	Pole adapter For use with: Videotec DBH04 (Axis 0216-041) Color: Black	125
Videotec Dome House Corner Mount DCWGH		0216-071	370466	Corner mount For use with: Videotec DBH04 (Axis 0216-041) Color: Black	85
VT DOME ADAPTER for AXIS 231D/232D ODBH24H249	EOL	0216-101	335240	Adapter plate to mount Axis 231/232 in Videotec's domehousing	149
VT dome adapter for AXIS 233D ODBH24H249		0216-131	347819	Adapter plate to mount Axis 233D in Videotec's domehousing. Includes cable 28256 for I/O	179
AXIS T92E05 PROTECTIVE HOUSING		0344-001	440498	Protective camera housing for P13XX, M11XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket, 5m network cable and screwdriver included.	179
AXIS T92E20 OUTDOOR HOUSING		0433-001	440497	Outdoor PoE camera housing with window-/camera heaters and fan for P13XX, M11XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket, 5m network cable and screwdriver included.	299
AXIS T92E23 THERMAL CAMERA HOUSING		0386-001	#N/D!	Aluminum outdoor thermal housing for AXIS Q1921 with 10mm, 19mm or 35mm lens. Wallbracket and sunshield included.	749
AXIS T92E24 THERMAL CAMERA HOUSING		0387-001	#N/D!	Aluminum outdoor thermal housing for AXIS Q1921 with 60mm lens. Wallbracket and sunshield included.	1 329
AXIS T93E05 PROTECTIVE HOUSING		5502-871	441861	The protective housing, AXIS T93E05, is compatible with the AXIS M11 series. Made of ASA polymer, it is IP66-rated and the operating temperature ranges between -20 °C to +50 °C (-4 °F to 122 °F). Wall bracket and sun shield are included.	100
AXIS T97A10 ENCLOSURE		5021-101	441862	IP66-rated enclosure for AXIS Q7401, AXIS P8221 and AXIS P7701. Operating temperature ranges between 0 °C to 45 °C (32 °F to 113 °F). Optional accessories for impact resistance and polemount are available.	69
AXIS T95A00 Dome Housing		5010-001	365672	Dome housing for AXIS 213, 214, 215 PTZ Network Cameras and AXIS 231D+, 232D+, 233D Dome Network Cameras. Includes clear and smoked bubble, heater with fan, power supply for network cameras. 100-240 VAC input.	549
AXIS T95A10 Dome Housing		5010-101	365675	Dome housing for AXIS 213, 214, 215 PTZ Network Cameras and AXIS 231D+, 232D+, 233D Dome Network Cameras. Includes clear and smoked bubble, heater with fan, power supply for network cameras 24VAC input. (Recommended power supply PS24)	499
AXIS T95A61 Wall Bracket		5010-611	365677	Wall bracket for AXIS T95A00 and T95A10 dome housing.	79
AXIS T95A62 Ceiling Bracket		5010-621	377298	Ceiling / Parapet bracket for AXIS T95A00 and T95A10 dome housing. Length: 48.5cm	169
AXIS T95A63 Extension Bracket		5010-631	376897	Extension bracket for AXIS T95A00 and T95A10 dome housing. Used with AXIS T95A62 Ceiling / Parapet bracket. Length: 27 cm	109
AXIS T95A64 Corner Bracket		5010-641	366507	Corner bracket for AXIS T95A00 and T95A10 dome housing. Requires AXIS T95A61 Wall bracket.	69
AXIS T95A66 Rotation Bracket		5010-661	376899	Rotation bracket for AXIS T95A00 and T95A10 dome housing. Used with AXIS T95A62 Ceiling / Parapet bracket.	69
AXIS T95A67 Pole Bracket		5010-671	366509	Pole bracket for AXIS T95A00 and T95A10 dome housing. Requires AXIS T95A61 Wall bracket.	99
INSTALLATION KIT AXIS P55XX/T95A		5502-991	454465	All required parts for installing an AXIS P553X into an AXIS T95A housing. Kit contents: Bracket, connector, I/O and audio cable, network cable and screws.	74
ACC Corner Mount AXIS 215 PTZ-E		5502-291	384718	Corner Bracket for AXIS 215 PTZ-E	49
ACC Pole Mount AXIS 215 PTZ-E		5502-301	384719	Pole Bracket for AXIS 215 PTZ-E	49
DIN Rail Accessories					
AXIS T91A02 DIN RAIL CLIP 77MM		5017-027	454466	DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	10
AXIS T91A02 DIN RAIL CLIP 86MM		5017-028	454467	DIN rail clip for AXIS M7014 and AXIS P7214	10
Fixed/Dome cameras accessories					
AXIS T8412 Installation Display		5018-002	404890	AXIS T8412 is a battery-powered handheld device that allows live view from Axis cameras or encoders. Used for quick and easy installation of Axis network products. Can also show analog video via BNC input. Includes casing, battery, charger, car charger, cable tester connector, protective rubber gasket, ethernet cable and analog BNC cable.	549
POWER SUPPLY AXIS T8412		5700-702	433726	Power supply for AXIS T8412 Installation Display	49
ACC YP3040 Pan Tilt Motor		5502-461	404897	YP3040 PAN TILT MOTOR is a compact PT motor for use with AXIS Q1755 Network Cameras and AXIS Q19 Series Network Thermal Cameras. Indoor and outdoor use. IP66-rated. 24VAC input. Compatible with AXIS T92A Housing and AXIS T92E Housing. YP3040 Wall bracket required. AXIS PS24 recommended.	399

ACC YP3040 Wall Bracket		5502-471	404899	Wall bracket for YP3040 Pan Tilt Motor. White	39
AXIS T91A06 PIPE ADAPTER 3/4-1.5"		5503-091	#N/D!	Pipe adapter step up from 3/4" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	10
PENDANT KIT AXIS P334X		5502-351	395975	With AXIS P33 Series PENDANT KIT it is possible to mount the AXIS P3343, AXIS P3343-V, AXIS P3344 and AXIS P3343-V Fixed Dome Network Camera on AXIS T91A Brackets or on standard 1.5" NPT threaded brackets. White	34
AXIS P33-VE Series Pendant Kit		5502-321	395977	With AXIS P33-VE Series PENDANT KIT it is possible to mount the AXIS P3343-VE and AXIS P3344-VE Fixed Dome Network Camera on AXIS T91A Brackets or on standard 1.5" NPT threaded brackets. White	44
DROP CEILING KIT CL AXIS P3343/4		5502-361	395982	Drop ceiling mount for AXIS P3343 and AXIS P3344 including clear transparent bubble. For indoor use	59
DROP CEILING KIT SM AXIS P3343/4		5502-371	395985	Drop ceiling mount for AXIS P3343 and AXIS P3344 including smoked transparent bubble. For indoor use	59
AXIS P33XX-VE 3/4" NPS ADAPT		5503-131	#N/D!	Stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	24
DROP CEILING KIT CL AXIS P3346		5502-781	433727	Drop ceiling mount for AXIS P3346 and AXIS P3367 including clear bubble. For indoor use	59
DROP CEILING KIT SM AXIS P3346		5502-791	433728	Drop ceiling mount for AXIS P3346 and AXIS P3367 including smoked bubble. For indoor use	59
Mounting Plate for AXIS P33 Series		5502-401	395987	Mounting plate for AXIS P3343, AXIS P3343-V, AXIS P3344 and AXIS P3344-V. Used when mounted on a single or double gang box.	24
MOUNTING BRACKET AXIS P33XX-VE		5700-691	441864	Original AXIS P33XX-VE mounting bracket for wall or hard ceiling.	24
1.5 inch to M30 Male adapter		5502-441	398790	Adapter to convert M30 to 1.5" thread. Used to convert VT Dome mounts to 1.5" NPT thread. Black color.	14
AXIS 225FD PENDANT KIT		5500-381	357728	With AXIS 225FD PENDANT KIT it is possible to mount the AXIS 225FD Network Camera on AXIS T91A Brackets, VT Dome mounts and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. Black	74
AXIS 225FD PENDANT KIT BLACK 1,5"NPT		5502-001	365686	With AXIS 225FD PENDANT KIT 1,5"NPT it is possible to mount the AXIS 225FD Network Camera on AXIS T91A Brackets and on 1,5" NPT threaded brackets. Black	64
Drop ceiling mount for AXIS 225		5003-001	342512	Drop ceiling mount for AXIS 225	94
Dome glass smoked for AXIS 225		5003-011	338560	Smoked glass bubble for AXIS 225FD.	56
Casing for AXIS 216FD/216MFD/P3301, smoked		5005-001	333524	Casing with smoked transparent cover fro AXIS 216FD/216MFD/P3301	24
Casing for AXIS 216FD/216MFD/P3301 black, clear		5500-821	364098	Interchangeable black casing for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras with transparent cover.	24
Casing for AXIS 216FD/216MFD/P3301 black, clear 10 pcs		5500-771	364097	Interchangeable black casing for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras with transparent cover. 10-pack.	229
AXIS M320X DOME KIT SM BLK		5503-191	#N/D!	Interchangeable black casing with smoked dome for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304.	24
AXIS 216FD/216MFD/P3301 +V PENDANT KIT BLACK		5500-881	365695	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets, VT Dome Brackets and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. Black	44
AXIS 216FD/216MFD/P3301 (-V) PENDANT KIT BLACK 1,5"NPT		5502-011	365696	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets and on 1,5"NPT threaded brackets. Black	34
AXIS 216FD/216MFD/P3301 (-V) PENDANT KIT WHITE		5500-891	365697	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets, VT Dome Brackets and on 1,5"NPT threaded brackets. Includes 1.5 inch to M30 Male adapter. White	44
AXIS 216FD/216MFD/P3301 (-V) PENDANT KIT WHITE 1,5"NPT		5502-021	365698	With AXIS 216FD PENDANT KIT it is possible to mount AXIS 212PTZ, 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras on AXIS T91A Brackets and on 1,5"NPT threaded brackets. White	34
Drop ceiling mount for AXIS 216FD/216MFD/P3301, clear		5005-031	354983	Drop ceiling mount kit for AXIS 216FD, AXIS M32 Series, AXIS P3301 and P3304 Network Cameras including clear transparent cover	56
AXIS M501X MOUNTING KIT		5800-121	#N/D!	Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	13
Drop ceiling mount for AXIS 216FD/216MFD/P3301, smoked		5005-041	345361	Drop ceiling mount kit for AXIS 216FD/216MFD/P3301 including smoked transparent cover	56
ACC DOME AXIS 216FD-V GLASS SMOKED		5005-061	358053	Vandal-resistant casing with smoked transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V	65
Videotec Verso Housing HPV42K1A000		0217-001	316659	Polycarbonate outdoor housing for the Axis 210 (indoor only), 211, 211A and 221 Network Camera. Heater and sunshield included, bracket and power supply not included.	108
Videotec Power Supply OHEPS19		0217-011	316658	Wide range power supply. For use with Videotec HPV42K1A000 (Axis 0217-001), for internal mounting to power the camera.	38
VT Wall bracket Balljoint WBJA		0217-021	328997	Wall bracket with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	20
VT Wall bracket Internal Cable WBOVA1		0217-031	343476	Wall bracket with internal cable channel. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	30
VT Ceiling Bracket Ball Joint WCM3A		0217-041	316301	Simple square tubing ceiling bracket with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	63
VT Ceiling Bracket Internal Cable WCM4A		0217-051	390864	Stylish round tubing ceiling bracket with internal cable channel. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	91
VT Ceiling Bracket Ball Joint WCM5A		0217-061	390865	Stylish round tubing ceiling bracket with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	102

VT Column Mount Ball Joint FWFCA		0217-071	390866	Column mount with ball joint. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	84
VT Pole Mount Adapter WSFPA		0217-081	333293	Pole mount adapter for AXIS T92A Housings. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	56
Vt Wall Bracket Adapter Plate WCPA		0217-091	384364	Wall bracket adapter plate. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	32
VT Corner Mount WCWA		0217-101	390867	Corner mount. For use with AXIS T92A00/T92A10, VT VERSO and AXIS HOV HOUSING VT	49
Videotec Wall Bracket Junction Box WBOV3A1		0217-111	#N/D!	Wall bracket, support plate and integrated junction box with internal cable channel. For use with Videotec HPV42K1A000 (Axis 0217-001).	166
Videotec Waterproof Junction Box OHEGB		0217-121	#N/D!	Waterproof junction box. For use with Videotec HPV42K1A000 (Axis 0217-001).	49
Verso Cool Outdoor Housing VT VERSO HOUSING FAN HPV42K0A017	EOL	0217-141	319800	Polycarbonate outdoor housing for the AXIS 210 (indoor only), 211, 211A and 221 Network Cameras, to be used in temperature up to +50C. Fan and sunshield included. Bracket, heater and power supply not included	178
VT POWER SUPPLY OHEGBPS1	EOL	0217-151	396356	Power supply for 0217-141	89
VT HEATER 110/230VAC OHPVH1	EOL	0217-161	396357	Heater for use with AXIS 0217-141. When used, 0217-141 can handle temp down to -20C	19
VT VANDAL RESISTANT HOUSING AVTPSC		0217-191	401486	Vandal-resistant indoor housing for AXIS 210/A, 211/A and 221	179
VT POWER SUPPLY OAVTPSCPS1		0217-211	408174	Power supply for 0217-191	49
VT HEATER KIT OAVTPSCH1		0217-221	393202	Optional heater for 0217-191	29
AXIS HOV POWER SUPPLY VT		0217-241	362570	Power supply for 0217-231. NOT FOR US	39
AXIS T92A00 Housing		5015-001	381477	Outdoor IP66 rated housing for AXIS 210/210A, 211/211A/211M/211W, 221 and 223M. Made of die-cast aluminium, the sunshield of ABS material. 110VAC-230VAC input and built in 12VDC camera power supply. NOT FOR US	199
AXIS T92A20 Housing		5015-202	390064	Outdoor High PoE powered IP66 rated housing for AXIS 210/210A, 211/211A/211M/211W, 221 and 223M. Made of die-cast aluminum, the sunshield of ABS material. Also includes heater, wall bracket with internal cable channel and AXIS T8121 single port High PoE midspan	359
Clamp mount for AXIS 206 and AXIS 207		5004-001	357591	Clamp to mount AXIS 206 and AXIS 207	8
AXIS 206/207 Vandal-resistant Housing	EOL	5006-001	326596	Vandal-resistant indoor housing for Axis 206/207 (not wireless).	179
ACC OUTDOOR ANTENNA KIT 211W		5500-311	354903	External antenna for AXIS 211W. Includes 3 m cable.	109
ACC LIGHTNING PROTECTOR 211W		5500-321	354906	Lightning protector for AXIS 211W	69
ACC MALE RJ45 for AXIS 209FD-R		5502-061	366511	Vibration resistant male RJ-45 connector suitable for RJ-45 version of AXIS M31XX-R and AXIS 209FD-R/MFD-R Network Cameras.	13
ACC MALE RJ45 for AXIS 209FD-R 10 pack		5502-051	366512	Vibration resistant male RJ-45 connector suitable for AXIS 209FD-R/MFD-R Network Camera. 10 pack	129
CONNECTOR M12 FEMALE 10PCS		5502-141	381384	Rugged, female D-coded M12 connector compatible with Connector M12 Female 4P, 209FD-R M12 /209MFD-R M12. Field installable with screw-in contacts. 10 pcs	99
CONNECTOR M12 MALE 10PCS		5502-131	381386	Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	99
CONNECTOR M12 FEM-FEM ADAPTER 100PCS		5502-691	448519	M12 connector adapter female-female (100 pcs)	1 099
COVER AXIS M30 SERIES BLACK 10PCS		5502-181	390058	Black cover with clear bubble for AXIS M30 Series. 10 pack	129
COVER AXIS M30 SERIES SILVER		5502-191	390059	Silver cover with clear bubble for AXIS M30 Series. 10 pack	129
COVER AXIS M30 SERIES GOLD 10PCS		5502-201	390060	Gold cover with clear bubble for AXIS M30 Series. 10 pack	129
COVER AXIS M30 SERIES MIX 10PCS		5502-341	390062	Mixed covers with clear bubble for AXIS M30 Series. Includes 3 black, 3 silver, 3 gold and 1 white cover.	129
MOUNT CLAMP AXIS M10 Series 10 PACK		5502-391	392740	Clamp to mount AXIS M10 series. 10 pack.	25
ACC TOP COVER AXIS 209FD BLK 10PCS		5502-481	404884	Replaceable black cover for AXIS 209FD/209MFD. 10 pcs	199
ACC PL ADAPTER FLAT AXIS M311X 10PCS		5502-541	418105	Optional plastic adapter for mounting AXIS M311X on flat surfaces. Used when the cable must enter from the side. 10 pack	24
ACC PL ADAPTER CURVED AXIS M311X 10PCS		5502-551	418106	Optional adapter for mounting AXIS M311X on curved surfaces. 10 pack	24
Lenses, analog cameras and camera stands					
C/CS lenses and acc.					
LENS CONVERTER 0.5X FOR Q1755		5500-501	406391	Super wide angle conversion lens for AXIS Q1755. Converts AXIS Q1755 lens to 2.55 -25.5mm.	149
LENS CONVERTER 2.2X FOR Q1755		5500-511	406394	Super telephoto conversion lens for AXIS Q1755. 2.2X. Converts AXIS Q1755 lens to 102mm. For use in full focal length.	169
Theia Fixedfocal Megapixel 1.7MM		5502-451	401025	Wideangle lens without barrel distortion. CS mount Fixedfocal Lens 1.7 mm DC-Iris for AXIS P1343 and AXIS P1344.	189
Pentax Varifocal Lens 5-50mm		5500-291	343013	CS mount Varifocal 5-50 mm DC-Iris for AXIS P1343 and AXIS 211/221	129
Pentax Varifocal Lens 5-50mm 10-pack		5500-941	364101	CS mount Varifocal 5-50 mm DC-Iris for AXIS P1343 and AXIS 211/221 in 10 pack	1 199
Tamron Varifocal 10-40mm		5502-121	375022	C mount Varifocal Lens 10-40mm DC Iris day and night corrected for AXIS 221. Includes C mount ring for AXIS 221.	159
Varifocal MegaPixel Lens 2.4-6mm		5500-871	364099	CS mount Varifocal Megapixel Lens 2.4-6mm DC Iris for AXIS P1344 and AXIS 211M/223M. Includes CS mount ring for AXIS 223M.	159
Varifocal MegaPixel Lens 5-50mm		5502-221	390868	CS mount Varifocal Megapixel Lens 5-50mm DC Iris for AXIS P1344 and AXIS 211M.	199

LENS CS 16MM F1.8 MP		5502-741	424645	Fixed Iris Megapixel Lens 16mm, F1.8, CS mount for AXIS M1103/4	39
LENS CS VF 2.2-6MM F1.3 DC-I MP		5502-751	424646	Varifocal 2.4-6mm DC-Iris Megapixel Lens, F1.3, CS mount for AXIS M1113/4	129
LENS CS VF 15-50MM F1.5 DC-I MP		5502-761	424647	Varifocal Mega Pixel DC-Iris Lens 15-50mm, F1.5, CS mount, for AXIS M1113/14	159
LENS CS 15-50MM F1.5 DC-I MP D/N	NEW	5503-421	#N/D!	Varifocal Megapixel DC-Iris Lens 15-50mm, F1.5, CS mount, Day/Night for AXIS Q1602.	159
ACC LENS CS 9-20MM F=1.6 P-IRIS 5MP		5502-801	430065	Varifocal 5 Mega Pixel P-Iris Lens 9-20mm, F1.6, CS mount, IR-corrected, for AXIS P1347 and AXIS P1346 firmware release 5.20 (or later)	329
M12 lenses					
LENS M12 MEGAPIXEL 2.8MM 10PCS		5502-101	375326	Megapixel lens 2.8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	139
LENS M12 MEGAPIXEL 3.6MM 10PCS		5502-151	378894	Megapixel lens 3.6mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	99
LENS M12 MEGAPIXEL 6MM 10PCS		5502-111	378896	Megapixel lens 6mm lens with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	99
LENS M12 MEGAPIXEL 8MM 10 PC		5502-411	394964	Megapixel lens 8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	99
LENS M12 MEGAPIXEL 16MM 10 PCS		5502-161	378897	Megapixel lens 16mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	99
LENS M12 MEGAPIXEL 10PCS		5502-421	433729	Mixed pack of M12 Megapixel lenses. Focal length: 2.8mm, 3.6mm, 6mm, 8mm and 16mm for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs=2 pcs of each lens.	99
LENS TOOL AXIS M311X 4PCS		5502-771	420101	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X. Content: Lens tool and Opening tool 4 pcs of each.	19
AXIS LENS CLOTH 10PCS		5502-661	419671	Axis accessory lens cloth. 10 pack	29
AXIS LENS CLOTH 50PCS		5502-721	425283	Axis accessory lens cloth. 50 pack	129
TA-LENS LWIR 10MM		5503-021	#N/D!	Thermal camera lens 10mm for AXIS Q1921	209
TA-LENS LWIR 19MM		5503-031	#N/D!	Thermal camera lens 19mm for AXIS Q1921	209
TA-LENS LWIR 35MM		5503-041	#N/D!	Thermal camera lens 35mm for AXIS Q1921	1 039
TA-LENS LWIR 60MM		5503-051	#N/D!	Thermal camera lens 60mm for AXIS Q1921	1 879
AXIS THERMAL LENS DEMO CASE		5503-011	#N/D!	Aluminum case for professional demonstrations of thermal lenses. 10mm, 35mm and 60mm LWIR TA-lenses are included. The fitting inside the case has tailor made compartments to fit AXIS Q1921 Thermal Network Camera, 1-port midspan, AXIS T91A21 stand and cables. The camera and accessories are not included. For more information see partner pages.	3 119
Stands					
Camera stand for AXIS 20X, plastic (BLACK)		5500-131	358896	Black plastic stand for AXIS 205, 206, 206M, 206W, 207, 207W Network Cameras	14
M10 STAND EXTENSION 10CM 10PCS		5502-701	424649	AXIS M10-series 10 cm stand extension. 10 pcs. Cable clip included.	24
AXIS T91A11 STAND WHITE		5017-111	427248	Plastic camera stand. Original stand for the AXIS M11-series.	13
AXIS T91A21 STAND WHITE		5017-211	433730	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	24
AXIS T91A21 STAND BLACK		5022-211	433731	Metal stand for wall or hard ceiling mount. Compatible with all standard tripod thread cameras e.g. AXIS Q17/19 series and AXIS P13 series.	24
Stickers					
SURVEILLANCE STICKER ENG 10PCS		5502-811	#N/D!	Axis branded sticker showing a Camera. Text: Video surveillance in operation	5
SURVEILLANCE STICKER ENG 50PCS		5502-821	#N/D!	Axis branded sticker showing a Camera. Text: Video surveillance in operation	15
Power supplies, cables, connectors and rack					
Power supplies					
ACC MAINS ADAP PS-P T-C		5502-241	387274	Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	29
EXTENSION CABLE PS-K 3M		5500-081	323375	Extension cable, 3M, for PS-K products	9
Extension cable PS-H - PS-L 1.8M		5500-141	339650	1.8 meter extension Cable for PS-H and PS-L products	6
AXIS PS24 ACC mains adaptor		5000-001	319828	24VAC power adapter for outdoor use together with 0216-001 or 0216-011. Note this is item is also listed under Dome/PTZ accessories. Use 5000-021 for AXIS 225FD	119
AXIS PS12 ACC mains adaptor		5000-021	355743	12V outdoor/indoor power supply, 5 meter (16.4 ft) input and output cable. Supplied without power plug.	159
MAINS ADAPTOR T90C10		5503-102	443947	Indoor mains power supply for the AXIS T90C10 illuminator. Output 24VDC 1.5A.	59
8 to 1 Power Splitter for Axis 2400/01+		20724	#N/D!	The 8 to 1 Power Splitter for 2400/01+. Feeds up to eight Axis 2400+/2401+. One 6.5 feet input cord and eight 2.9 feet output cords. Snap-mount for 35mm DIN rails. NOTE: No power supply included.	149
Cables, adaptors					
Audio I/O Cable for AXIS P33 Series 5m		5502-331	398166	Audio and I/O extension cable for AXIS P33 series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Femal. 5 meter.	29
Cable, extension PS-D		18607	#N/D!	Extension cable for Power Supply, 3.3 meters, for PS-D	9
Cable, null modem		18609	#N/D!	Serial NULL Modem cable for 2100, 2110, 2120, 2420	17
Cable - Visca to Server		18619	#N/D!	Cable to connect PTZ control of Sony EVI VISCA to Video server, 3 meters	18

Cable - Visca to Visca		18621	#N/D!	Extension cable for PTZ control of Sony EVI VISCA, 3 meters	18
Cable adapter - Y/C to BNC		21832	#N/D!	Cable adapter to connect a Y/C (S-Video) cable to the Axis 241S Video Server. Same as 21833 but for US	16
Cable adapter - Y/C to BNC		21833	428103	Cable adapter to connect a Y/C (S-Video) cable to the Axis 241S Video Server. Same as 21832 but for EUR	16
BNC to RCA adaptor		5500-441	381382	4 pack of BNC to RCA adaptors	19
CABLE SEALING IP65 FOR Q8108-R		5502-711	430066	Accessory cable sealing to meet IP65 rating for Q8108-R.	199
MAINS ADAPTER AXIS Q8108-R		5502-071	437232	Indoor mains adapter for powering an AXIS Q8108-R when not installed in a vehicle	60
Rack mount 2400/2401		19273	#N/D!	19" Rack mount holder for up to 8 2401/2400 Video Servers.	299
Power over LAN/Power over Ethernet/Wireless devices					
Power Over LAN Active Splitter	EOL, product replacement 5014-501	0170-001-01	275782	Use with Power Over LAN Midspans to enable Power Over LAN for AXIS 213 and AXIS 230. Output 12 VDC. The Power over LAN Active Splitter is not IEEE 802.3af compliant. It works only with the AXIS POE MIDSPAN 1-PORT.	89
AXIS PoE Active Splitter 5V AF		5008-001	331560	Power over Ethernet (802.3af) compatible. Use with Power over Ethernet-midspans or PoE-enabled switches to enable Power over Ethernet for AXIS 206, 207, 207W and 207MW.	79
AXIS PoE Midspan 8-port		5012-002	363015	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing, Replacing 0169-012-01	499
AXIS PoE Midspan 16-port		5012-012	363016	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing. Replacing 0169-002-01	699
AXIS POE Midspan 1-port		0226-002	307951	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length 328ft/100m/ Supports single Axis Network Camera/Video Server. Plastic casing	65
PoE Active Splitter	EOL, products replacement 5014-501 or 5014-511	0227-001	310035	Power over Ethernet (802.3af) compatible. Use with Power Over LAN Midspans or PoE - enabled switches to enable Power over LAN for Axis 210, 2100, 2110, 2120, 2420, 2400+, 2401+, 2411, 241Q, 241S 250S Output 18 VDC.	89
T8121 High PoE Midspan 1-Port	EOL	5014-002	383354	High PoE 1-port midspan (802.3.at pre-standard). Compliant with PoE 802.3af. A High PoE 802.3at pre-standard splitter (AXIS T8126/T8128) is required.	65
AXIS T8122 DC 30W MIDSPAN		5023-221	#N/D!	PoE midspan for PTZ dome- and fixed outdoor cameras. IEEE802.3at and IEEE802.3af compliant. input 12-24 VDC or 50-57 VDC. Temp spec: -20 °C to 65 °C (-4 °F to 149 °F).	89
AXIS T8123 High PoE 30W Midspan 1-Port		5014-202	419672	High PoE 1-port midspan 30W. Compliant with 802.3.at and PoE 802.3af. Can be used with AXIS T8126/T8128 splitter. Replacing AXIS T8121	65
T8126 High PoE Splitter 12V		5014-501	376767	12V DC High PoE splitter (802.3.at pre-standard). Requires either a AXIS T8121 midspan (max 24W output) or a 802.3af PoE midspan (max 12W output) Adapter cable for AXIS 210, 213PTZ, 214PTZ, 215PTZ and 225FD is included.	65
T8128 High PoE Splitter 24V		5014-511	376766	24V DC High PoE splitter (802.3.at pre-standard). Requires High PoE midspan (AXIS T8121). Adapter cable for AXIS 231D+, 232D+ and 233D is included.	65
IR Illuminators					
IR Illuminator 850NM 30 DEG	EOL, Use AXIS T90A Series	20805	288733	Semi-Cover IR Illuminator for use with the AXIS 2420 Network Camera - IR Sensitive, AXIS 221 Day Night Network Camera, AXIS 225FD, AXIS 213 PTZ, AXIS 214 PTZ, AXIS 232D, AXIS 230 MPEG 2	449
IR Illuminator 850NM 60 DEG	EOL, Use AXIS T90A Series	20810	288735	Semi-Cover IR Illuminator for use with the AXIS 2420 Network Camera - IR Sensitive, AXIS 221 Day Night Network Camera, AXIS 225FD, AXIS 213 PTZ, AXIS 214 PTZ, AXIS 232D, AXIS 230 MPEG 2	449
IR Illuminator 940NM 20 DEG	EOL	20815	288737	Covert IR Illuminator for use with the AXIS 2420 Network Camera - IR Sensitive, AXIS 221 Day Night Network Camera, AXIS 225FD, AXIS 213 PTZ, AXIS 214 PTZ, AXIS 232D, AXIS 230 MPEG 2	449
IR Illuminator 940NM 50 DEG	EOL	20820	285398	Covert IR Illuminator for use with the AXIS 2420 Network Camera - IR Sensitive, AXIS 221 Day Night Network Camera, AXIS 225FD, AXIS 213 PTZ, AXIS 214 PTZ, AXIS 232D, AXIS 230 MPEG 2	449
AXIS T90A01 IR-LED 50 DEG POE		5013-011	375032	850 nm semi-cover IR LED Illuminator for use with the Axis Day/Night network cameras. Fixed angle 50 degrees. Range 14 meters. Input: Power over Ethernet(PoE). Consumption : 10 W	349
AXIS T90A11 IR-LED 50 DEG		5013-111	390870	850 nm semi-cover IR LED Illuminator for use with the Axis Day/Night network cameras. Fixed angle 50 degrees. Range 14 meters. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 10 W Cable length 2.5m	399
AXIS T90A20 IR-LED 120-180 DEG		5013-201	368781	850 nm semi-cover IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 120 to 180 degrees. Range 16 meters in 120 degrees and 11 meters in 180 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 20 W Cable length 2.5m	399
AXIS T90A21 IR-LED 50-100 DEG		5013-211	368791	850 nm semi-cover IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 50 to 100 degrees. Range 28 meters in 50 degrees and 18 meters in 100 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 20 W Cable length 2.5m	399
AXIS T90A33 IR-LED 10-20 DEG		5013-331	5013-331	850 nm semi-cover IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 10 to 20 degrees. Range 150 meters in 10 degrees and 100 meters in 20 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 50 W Cable length 2.5m	799

AXIS T90A32 IR-LED 30-60 DEG		5013-321	408198	850 nm semi-covert IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 30 to 60 degrees. Range 80 meters in 30 degrees and 53 meters in 60 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 50 W Cable length 2.5m	799
AXIS T90A40 IR-LED 120-180 DEG		5013-401	368835	850 nm semi-covert IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 120 to 180 degrees. Range 64 meters in 120 degrees and 42 meters in 180 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 80 W Cable length 2.5m	1 299
AXIS T90A42 IR-LED 30-60 DEG		5013-421	408199	850 nm semi-covert IR LED Illuminator for use with the Axis Day/Night network cameras. Adjustable angle between 30 to 60 degrees. Range 160 meters in 30 degrees and 106 meters in 60 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 80 W Cable length 2.5m	1 299
AXIS T90A66 Pole Bracket		5013-661	386032	Pole Bracket for AXIS T90A illuminators	69
AXIS T90A61 BRACKET SINGLE		5013-611	419674	Mounting bracket for one AXIS T90A illuminator.	39
AXIS T90A63 BRACKET WALL L MOUNT		5013-631	424650	L shaped wall bracket which provides up/down and left/right adjustment when used with the standard bracketry on AXIS T90A series illuminators.	34
AXIS T90A62 BRACKET TWIN		5013-621	419675	Mounting bracket for two AXIS T90A illuminators.	49
AXIS T90C10 FIXED DOME IR-LED		5024-101	442476	IR-illuminator for AXIS P334X-VE cameras. 18-56 VDC input. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, IK-10 impact resistant. Premounted 5m power cable cable with gaskets.	299
AXIS T90C20 FIXED DOME IR-LED		5024-201	442477	IR-illuminator for AXIS P334X-VE cameras. PoE IEEE802.3af compliant. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, IK-10 impact resistant. Premounted 5m network cable cable with gaskets.	299
White LED Illuminators					
AXIS T90A06 W-LED 50-100 DEG POE	EOL	5013-061	375034	White LED Illuminator for use with the Axis network cameras. Fixed angle 50 degrees. Range 13 meters. Input: Power over Ethernet (PoE). Consumption : 10 W	349
AXIS T90A16 W-LED 50		5013-161	390871	White LED Illuminator for use with the Axis network cameras. Fixed angle 50 degrees. Range 13 meters. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 10 W Cable length 2.5m	349
AXIS T90A26 W-LED 50-100 DEG		5013-261	368836	White LED Illuminator for use with the Axis network cameras. Adjustable angle between 50 to 100 degrees. Range 20 meters in 50 degrees and 13 meters in 100 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 25 W Cable length 2.5m	449
AXIS T90A37 W-LED 30-60 DEG		5013-371	368837	White LED Illuminator for use with the Axis network cameras. Adjustable angle between 30 to 60 degrees. Range 42 meters in 30 degrees and 28 meters in 60 degrees. Includes power supply with photocell and wall / ceiling bracket. Input : 100-240 VAC Consumption : 50 W Cable length 2.5m	799